



	Theater		Conference		Classroom / Meeting Room			
	Full HD - WUXGA		Laser Light Source	Laser Light Source	Full Featured		Entry Level	
Note: Photos are not sized to scale.								
Model	EK-833DU / EK-831DU	EK-1000LU / EK-850U	EK-700LU	EK-600LU	EK-308U / EK-308UA	EK-309W	EK-130U	
IN STOCK (as of May 15, 2023)	17 / 7	10 / 64	121	270	68 / 9	3	23	
Key Features	High brightness, vivid color DLP Laser Projectors; HDBaseT input; IP6X compliant sealed optical engine; Full 360° installation capability	High performance, low maintenance 3LCD Laser Projector; 4K Scaler; HDBaseT input; Filter-less design; Full 360° installation capability	High brightness and contrast 3LCD Laser Projector; 4K Scaler; HDBaseT input; Full 360° installation capability;	High brightness and contrast 3LCD Laser Projector; 4K Scaler; HDBaseT input; Full 360° installation capability;	High brightness and contrast 3LCD Laser Projector; 4K Scaler; HDBaseT input; Full 360° installation capability;	High brightness and contrast portable; HDMI input with Mobile High-Definition Link; Lens shift and corner keystone correction	Full featured, high brightness portable; Lens shift; Corner keystone; pin cushion & barrel image correction	20,000 Hour Infinity Lamp Technology; 2x HDMI port; Corner Keystone Correction; 16W Audio System
Display Technology	1-chip DLP®	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	
Price (MSRP)	\$18,720 / \$15,840	\$12,240 / \$9,360	\$4,025	\$3,150	\$2,010 / \$1,895	\$1,655	\$1,510	
Brightness	13,000 / 11,000 lumens	10,000 / 8,500 lumens	7,000 lumens	6,000 lumens	6,000 lumens	6,000 lumens	5,000 lumens	
Native Resolution	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WXGA (1280x800)	WUXGA (1920x1200)	
Max. Computer Input	WUXGA	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	WUXGA	WUXGA	WUXGA	
Max. Video Input	1080p	1080p	1080p	1080p	1080p	1080p	1080p	
Contrast Ratio	100,000:1	100,000:1	5,000,000:1	5,000,000:1	10,000:1	10,000:1	15,000:1	
Panel Size (Diagonal)	0.67"	0.76" inorganic	0.64" inorganic	0.64" inorganic	0.64" inorganic	0.64" inorganic	0.64" inorganic	
Lens Type (Throw: Width)	Supplied without lens	Supplied without lens	1.22-1.98:1	1.20-2.00:1	EK-308U: 1.07-1.75:1 EK-308UA: 1.29-2.11:1	1.07-1.75:1	1.26-2.09:1	
Image Offset / Lens Shift	U/D 60%; L/R 10%	Lens Shift: U/D +50-10%; L/R 20%	Lens Shift: Up: 60%; L/R: 29%	Lens Shift: Up: 60%	Lens Shift: U/D: 45%; L/R: 10%	Lens Shift: U/D: 45%; L/R: 10%	Fixed Offset: 8.71:1	
Keystone Correction	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 15°	U/D 30°; L/R 15°	U/D 30°; L/R 30°	
Inputs	Dsub15 x 1; HDMI x 1; DVI-D (w/ HDCP) x 1; BNC x 5; 3G-SDI BNC x 1; RCA x 1; S-Video x 1; HDBaseT RJ45 x 1; 3D Sync Mini Din 3 x 1; USB-A x 1; USB-B x 1	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;	Dsub15 x 1; HDMI x 2; HDBaseT RJ45 x 1; USB-A x 1; USB-B x 1; MiniStereo x 1	Dsub15 x 1; HDMI x 2; RCA x 1; HDBaseT RJ45 x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 2; HDMI x 2; RCA x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 2; HDMI x 2; RCA x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 1; HDMI x 2; RCA x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	
Outputs	Dsub15 x 1; 3G-SDI BNC x 1; 3D Sync Mini Din 3 x 1	HDMI x 1; Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	
Sound System	-	-	16 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	10 Watt; 1.4" Speaker x 1	10 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	
Lamp Life	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 4,000 hours	Up-to 4,000 hours	Up-to 20,000 hours	
Lamp Part Number	-	-	-	-	23040013	23040013	22040012	
Fan Noise	As low as 39 dBa	As low as 27 dBa	As low as 27 dBa	As low as 27 dBa	As low as 35 dBA	As low as 35 dBA	As low as 30 dBA	
Air Filter	-	-	Standard	Standard	Standard	Standard	Standard	
Maximum Pitch	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°	± 30° U/D	± 30° U/D	± 10° U/D	
Weight	58.4 lb (26.5 kg)	52.9 lb (24 kg)	17.0 lb (7.7 kg)	11.5 lb (5.2 kg)	9.9 lb (4.5 kg)	9.9 lb (4.5 kg)	7.0 lb (3.2 kg)	
Ceiling Mount PN	0173-5042	0173-5042	0173-4293	0173-4293	0173-4367	0173-4367	0173-4293	

Quantities listed reflect stock level at start of business May 15, 2023. Product is available on a first come first serve basis.

Eiki International, Inc.

22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 · Tel: 800-242-3454 · E-Mail: usa@eiki.com · Website: www.eiki.com

Prices and specifications are subject to change without notice. *Projector Warranty: 3 Years or 6,000 Hours (whichever occurs first). See warranty card for full details.

Optional Lenses

EK-850LU / EK-1000LU Optional Lenses

Model #	T/W Ratio	List Price	In Stock
AH-EC22030	0.79-1.11:1	\$3,040.00	31
AH-EC21020	1.30-3.02:1	\$2,045.00	25
AH-EC21030	1.46-2.95:1	\$620.00	40
AH-EC24010	2.99-5.93:1	\$3,620.00	0
AH-EC23030	4.59-7.02:1	\$2,275.00	0

EK-831DU / EK-833DU Optional Lenses

Model #	T/W Ratio	List Price	In Stock
AH-AC22060	0.76-0.95:1	\$2,735.00	8
AH-AC22070	1.14-1.71:1	\$3,660.00	4
AH-AC21020	1.61-2.42:1	\$2,250.00	7
AH-AC24020	2.37-3.60:1	\$3,970.00	7
AH-AC23020	3.53-5.65:1	\$3,640.00	0
AH-AC23030	5.52-8.83:1	\$4,790.00	6

Audio Conference System



Model #	Description	List Price	In Stock
EMMU02	Main Processing Unit	\$1,225.00	2
EMC02	Chairman Mic	\$360.00	6
EMD02	Delegate Mic	\$325.00	9
EM63	Antenna	\$295.00	7
EM48	Charger Case	\$360.00	2

Quantities listed reflect stock level at start of business May 15, 2023. Product is available on a first come first serve basis

Eiki International, Inc.

22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 · Tel: 800-242-3454 · E-Mail: usa@eiki.com · Website: www.eiki.com
 Prices and specifications are subject to change without notice. *Projector Warranty: 3 Years or 6,000 Hours (whichever occurs first). See warranty card for full details.