




C735PS

7,300 Lumens / 3LCD / Laser Light Engine
 1080p with 4K Enhancement / HDR10 Support
 Short Throw Lens (0.68-0.82:1)

C735PS

7,300 center lumens bright with 80% uniformity and a 5,000,000:1 contrast ratio.
 1080p with 4K Enhancement doubles HD video resolution for sharper picture.
 Short Throw Lens (0.68-0.82:1) with 1.2:1 manual zoom.
 Compatible with inputs up-to 1080p, WUXGA and 4K. HDR10 support.
 Supports digital video input in all color standards up-to 4K.
 Horizontal, Vertical & Corner Keystone Correction.
 Pincushion/Barrel & 6 point Geometric Correction.
 Horizontal & Vertical Manual Lens Shift. Wired PjLink network control.
 Displays 4:3, 16:9 and 16:10 aspect ratios. Supports most HDTV resolutions.
 Built-in 16 Watt sound system. Closed Caption decoding (NTSC).
 Side-accessed air filter for ease of maintenance.
 Auto input selection. Built-in Test Patterns.
 Security bar. Kensington® MicroSaver® security slot. PIN lock.
 3 year Projector warranty. 20,000 hour Laser Light Engine warranty.



Included Accessories:

Quick Start Guide, HDMI Cable, Detachable Power Cord, Remote Control

Optional Accessories:

Replacement Filter, Ceiling Mount, Ceiling Post and Plate

Specifications: Model C735PS

Brightness	7,300 Center Lumens	Video Formats	NTSC / PAL / SECAM
Contrast Ratio	5,000,000:1	Video Input Digital	480p, 576p, 720p, 1080i/p, 4K UHD, 4K DCI
Illumination Uniformity	80%	Image Signal Resizing	Smart Scaling Technology
Resolution and Aspect Ratio	1080p with 4K Enhancement, 16:9	Image Signal Inputs	HDMI x 2
Color Reproduction	10-bit (16.7 million colors)	Digital Video (w/ HDCP)	RJ45 x 1
Projection Light Source	Laser (Blue) + Phosphor	HDBaseT	USB Type A x 2
Estimated Light Source Life	20,000 hours	USB-A	
Total Pixels	6,220,800 (1920x1080) x 3	Outputs	
Imaging System	0.64 in (16 mm) inorganic LCD Panels x 3	Digital Audio	S/PDIF x 1
Scanning Frequency	Auto: H Sync. 15-135 KHz, V Sync. 24-85 Hz	Audio Output	Variable, Stereo: MiniStereo x 1
Pixel Clock	up-to 160 MHz	Speaker	Mono: 16 Watt
Lens	Attached - Manual Zoom and Focus	Fan Noise (Eco / Normal)	29 dB / 39 dB
Lens Specs	f: 1.7-1.8; FL: 0.38-0.46 in (9.66-11.65 mm)	Cabinet Size (HxWxD) - excluding legs	5.4 x 15.9 x 14.1 in (13.7 x 40.5 x 35.8 cm)
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width 0.68-0.82:1	Weight	17.4 lb (7.9 kg)
Image Diagonal	50-300 in (127-762 cm)	Packaged Cabinet Size (HxWxD)	10.0 x 19.9 x 19.1 in (25.5 x 50.5 x 48.4 cm)
Image Width	3.6-21.8 ft (1.11-6.6 m)	Packaged Weight	22.9 lb (10.4 kg)
Throw Distance	2.5-17.8 ft (0.75-5.44 m)	Operating Temperature	41-104°F (5-40°C)
Lens Shift	V: + 50% H: +/- 23%	Electrical Safety Compliance	IEC / UL / cUL
Projector Elevation Adjustment (legs)	Up-to 3.5°	Electromagnetic Compatibility	FCC Class B, CE Mark
Maximum Pitch	Up-to 360° Installation	Power Requirements	100-240V AC, 50/60 Hz
Vert/Horiz. Keystone Correction	Digital: V: +/- 30° H: +/- 25°, Corner Keystone	Power Consumption	0.5 W in Eco Standby mode, up-to 390 W
Image Orientation	Normal, Reversed, Inverted	Heat	1,330 BTU
Local Control / Power Management	Full Function / Auto Shutdown	Security Facilities	Kensington® Security Slot
Remote Control	Wireless x 1	User Maintenance	Clean Filter
RS-232 Control	Dsub9 x 1	Limited Warranty: to the original end use customer only	
LAN Port	RJ45 x 1	Projector	*3 years / 6,000 hours use
Computer Input in Pixels	up-to 3840X2160 (16:9), 4096X2160 (17:9)	Laser Light Engine only	*3 years / 20,000 hours use
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA		*(whichever occurs first)
Digital Wide Inputs	4K, WUXGA, WSXGA+, WXGA		

EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.

Specifications subject to change without notice. © Eiki International Inc. Issued February 17, 2026
 Eiki International Inc., 22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 Tel: 800-242-3454 Email: usa@eiki.com