



EIP-1

1400 ANSI Lumens!

Get the high contrast and low pixilation of DLP™ technology in an affordable, microportable projector.



EIP-1

- Weighs about 4.4 lbs! Footprint smaller than a sheet of paper!
- 1400 ANSI Lumens, 85% uniformity, and 900:1 contrast ratio.
- True XGA resolution. SXGA, XGA, SVGA, and VGA compatible.
- If not needed, the AV Module can be detached for greater portability.
- Smart data compression / expansion, and video scaling.
- Easy to use and convenient manual zoom and focus lens.
- Preset image offset. Vertical digital keystone correction.
- Accepts Composite, S, and Component Video in all major standards.
- Displays both Normal 4:3 and Widescreen 16:9 ratio video formats.
- Supports HDTV at 1080i, 1035i & 720p. Supports SDTV at 480i/p & 575i/p.
- Slideshow Page Up/Down on remote control. Factory defaults reset.
- Wireless remote with mouse and Laser pointer. 14X digital zoom.
- Optional DVI Digital Computer Input Cable.
- 3 Year* Projector Warranty!

EIKI Means Projectors ... and more!

EIP-1



DLP™ Technology.
Digital Light Processing™.
Technology based subsystem.



Lamp Contains Mercury. Do not put in trash. Dispose-of-as Hazardous Waste, according to Local, State or Federal Laws.



INCLUDED ACCESSORIES:

Quick Start Guide. Owner's Instruction Manual. North America 3-prong grounded and polarized AC Power Cord & 2-prong polarized Adapter with ground wire. European 2-prong AC Power Cord. Lens Cover & Retainer. VGA-type Computer In/Out Cable (HD15 ~ HD15). Computer Audio In/Out Cable (Stereo Mini ~ Stereo Mini). S-Video cable (Mini-DIN~Mini-DIN). Composite Video & Audio Input Cable (RCAX3 ~RCAX3). Mouse Cable (USB-A ~USB-B). Wireless Remote Control with Mouse and Laser Pointer & 2 AAA Batteries. Padded Carry Bag with shoulder strap. "Direct Connect" cable: Analog Computer & Mouse Input Cable (M1DA~HD15 & USB-A) (this permits use of the projector without the AV Module: no audio).

OPTIONAL ACCESSORIES:

Replacement Lamp. Component Video Input Cable HD15~RCAX3). Ceiling Mount. Ceiling Post and Plate. "Direct Connect" cables: Digital Computer & Mouse Input Cable (M1DA~DVI-D & USB-A); and SDTV (480p & 575p) & HDTV (720p, 1035i & 1080i) Input Cable (M1DA~RCAX3) (these permit use of the projector without AV Module: no audio).



Specifications subject to change without notice.

©2004 EIKI International, Inc. Printed in the USA. 02/01/04

SPECIFICATIONS: EIP-1

Screen Brightness	1,400 ANSI Lumens
Illumination Uniformity	85%+
Size of Color Palette	16.7 Million
Contrast Ratio	900:1 (Full ON/OFF)
Horizontal Resolution	800 TV Lines
Projection Lamp	150 Watt VIP
Estimated Lamp Life	1,500 Hours
Imaging System	0.7" DDR XGA DMD
Screen Pixels	1024 x 768 in stripe configuration
Total Pixels	786,432 (1024 x 768)
Lens Type	Manual Zoom and Focus
Lens Specs	Speed: f:2.4~2.6; FL: .95~1.33 in. (24~28.8 mm)
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width: 1.72~2.00:1
Image Diagonal	30~300 in. (76.2~762 cm)
Image Width	2.0~20 ft. (.61~6.1 m)
Throw Distance	3.4~40.0 ft. (1.04~12.2 m.)
Front Elevation/Maximum Tilt	up to 11° up / +/- 20°
Anti Keystone	Fixed Image Offset, Ratio (Top:Bottom) approx. 10:0
Vertical Keystone Correction	Digital, up to 20° up or down
Scanning Frequency	Auto: H Sync. 15-100kHz; V Sync. 50-100Hz
Dot Clock	140 MHz
Image Orientation	Normal, Reversed, Inverted
Local Control	Full Function
Remote Projector & Mouse Control	Wireless (Infra Red) with Laser Pointer x 1
Mouse Port	USB Type B x 1
Computer Native Resolution	1024 x 768 (XGA)
Computer: Compatibility	SXGA, XGA, SVGA, VGA
Computer: Formats	1280x1024, 1024x768, 800x600, 640x480
Computer: Higher Resolutions	Displayed Smart Compressed
Computer: Lower Resolutions	Displayed Smart Expanded
Video Color Systems	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N
Video Resolutions	480i/p, 575i/p, 720p, 1035i, 1080i
Video Formats Supported	Normal 4:3 and Wide Screen 16:9
Video: Image Sizing	Video Scaling Technology
Computer In:	
1. Analog:	M1DA x 1
2. Analog:	HD15 x 1, Audio: Stereo - MiniStereo x 1
Video In:	
1. Composite:	RCA x 1 (Y)
2. S-Video:	S-Video x 1 (Y/C)
3. Component (i/p):	HD15 x 1 (computer) (YCbCr)
Audio:	Stereo: RCA x 2 (L&R)
Computer Audio Out	Stereo - MiniStereo x 1
Audio: Amplifier:	Mono: 2.5 Watt RMS x 1
Audio: Built In Speakers	1.6 in. x 1.1 in. (4 x 2.8 cm) x 1
Operating Noise	39 dBA typical
Cabinet Size (HxWxD)	2.8 x 7.6 x 9.0 in. (69 x 193 x 229 mm)
w/AV module	2.8 x 7.6 x 10.8 in. (69 x 193 x 274 mm)
Weight: Projector only	3.85 lbs. (1.75 kg)
w/AV module	4.4 lbs. (2.0 kg)
Packaged Size (HxWxD)	12.8 x 12.5 x 14.1 in. (325 x 318 x 357 mm)
Packaged Weight	9.7 lb (4.4 kg)
Power Requirements	100-240V AC, 50/60Hz
Power Consumption / Heat	220 W / 751 BTU/hr (189 Kcal/hr)
Power Cord	6' (1.8M) Type 3, Detachable
Safety Compliance	cULus Listed
Security Facilities	Kensington® Security Slot
Operating Temperature	41~95°F (5~35°C)
User Maintenance	Replace Lamp
Warranty: Projector	3 Yr. / 6000 Hr. *(Parts/Labor to Correct Defects)
Warranty: Lamp	90 Days (Failed Lamp Replaced Pro-Rata)

* whichever occurs first

Talk to your EIKI Dealer... the "pro" in projection.



Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130

Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8

Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

Fax-on-Demand: (Toll Free) 877-345-4329 <http://www.eiki.com>