

2,500 ANSI Lumens • XGA • 1-chip DLP®

EIP-XSP2500

XGA Short Throw Projector



Get the film-like imaging of DLP® technology with new BrilliantColor™ expanded-spectrum color reproduction in a classroom projector.



Key Features:

- △ 2,500 ANSI lumens, 80% uniformity and 1600:1 contrast ratio.
- △ Native XGA resolution. Compatible with inputs up-to SXGA and WXGA.
- △ Supports analog video input in all color standards up-to 1080i.
- △ 1-chip DLP® imaging technology delivers a "seamless" high-contrast image.
- △ 6-segment color wheel and BrilliantColor™ color processing.
- △ Short throw fixed focal length lens with manual focus.
- △ Fixed image offset. Vertical digital keystone correction.
- △ Two Dsub15 computer inputs, plus one Dsub15 computer monitor output.
- △ Accepts composite, component, and S-Video in all major standards.
- △ Built-in wired LAN connection for projector monitoring and control.
- △ Low maintenance: filter free operation and long life lamp.
- △ Eco mode operation reduces power consumption and fan noise.
- △ Kensington® security slot.
- △ Wireless remote control. Digital zoom function.
- △ 3 year projector warranty.



EIKI
Projectors... and more!



EIP-XSP2500 SPECIFICATIONS:

Brightness up-to 2,500 ANSI Lumens
 Contrast Ratio up-to 1600:1
 Illumination Uniformity (corner to center) 80%
 Resolution and Aspect Ratio XGA (1024 x 768), 4:3
 Color Reproduction 8 bit (16.7 million colors)
 Projection Lamp 230 watts P-VIP
 Estimated Lamp Life up-to 5,000 hours
 Imaging System 0.55" (14 mm) 1-chip DLP x 1
 Total Pixels 1024 x 768
 Scanning Frequency Auto: H: 15 ~ 82 kHz; V: 50 ~ 85 Hz
 Pixel Clock up-to 165 MHz
 Lens Attached - Fixed FL, Manual Focus
 Lens Specs Speed: f: 2.6; FL: 0.668 in (17 mm)
 Lens Ratios Throw:Width: 0.62:1
 Image Diagonal 30 ~ 300 in (76.2 ~ 762 cm)
 Image Width 2.0 ~ 20 ft (0.61 ~ 6.1 m)
 Throw Distance 1.2 ~ 12.4 ft (0.38 ~ 3.78 m)
 Projector Elevation Adjustment (legs) up-to 9° Up
 Maximum Pitch up-to 360° Up or Down
 Vertical Lens Shift (% of image height) Adjustable 52.0 ~ 54.5% Up
 Vertical Keystone Correction Digital: up-to 20° Up or Down
 Image Orientation Normal, Reversed, Inverted
 Local Control / Power Management Full Function / Auto Shutdown
 Remote Projector Control Wireless (Infra Red) x 1
 RS232 Control Port Dsub9 x 1
 LAN Port RJ45 x 1
 Computer Input in Pixels up-to 1280 x 1024 (4:3), 1280 x 800 (16:10)
 Analog 4x3 Inputs SXGA, XGA, SVGA, VGA, MAC
 Analog Wide Inputs WXGA
 Video Formats NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N
 Image Signal Resizing Smart Scaling Technology
 Video Input Analog 480i/p, 575i/p, 720p, 1080i


Image Signal Inputs:
 1 Computer (VGA IN 1) Dsub15 x 1
 Component Video (with optional adapter), 3RCA
 2. Computer (VGA IN 2) Dsub15 x 1
 Component Video (with optional adapter), 3RCA
 3. S-Video S-Video x 1
 4. Composite Video RCA x 1
 Audio Signal Inputs
 Audio Input Stereo: MiniStereo x 1
 Outputs
 Computer Monitor Dsub15 x 1
 Amplifier 10 watts
 Speaker 1.3 in (3.2 cm) x 1 (Mono)
 Fan Noise as low as 34 dBA
 Cabinet Size (HxWxD) 3.4 x 8.1 x 11.0 in (8.5 x 20.6 x 28.0 cm)
 (excluding legs)
 Weight 6.6 lb (3.0 kg)
 Packaged Size (HxWxD) 7.6 x 13.6 x 14.2 in (19.4 x 34.5 x 36 cm)
 Packaged Weight 10.1 lb (4.6 kg)
 Power Requirements 100 ~ 240V AC, 50/60 Hz
 Power Consumption 0.9 watts in Eco Standby mode, up-to 300 watts
 Heat 3.4 BTU/hr in Eco Standby mode, up-to 1,024 BTU/hr
 Power Cord 6 ft (1.8 m) Type C13, Detachable
 Electrical Safety Compliance IEC / UL / cUL
 Electromagnetic Compatibility FCC Class B, CE Mark
 Security Facilities Kensington® Security Slot
 Operating Temperature 41 ~ 95°F (5 ~ 35°C)
 User Maintenance Change Lamp
 UPC 4571194674316
 Limited Warranty: to the original end-use customer only
 Projector 3 years
 Lamp 6 months ownership / 500 hrs use (which ever occurs first)

EIKI® is a registered trademark of Eiki International, Inc. Kensington® is a registered trademark of ACCO Brands Corporation.

**0.62:1 Throw Ratio. Fill a 60" wide screen from 38".
 Perfect for classroom interactive whiteboard use.
 Great for "corner-of-the desk" presentations.**



Ready to connect and project.



EIP-XSP2500 • XGA • 1-Chip DLP® Projector.



Easily mounts to ceiling.



Fill a 60" wide screen from 38".



Just connect and project.

INCLUDED ACCESSORIES:

Owner's Manual on CD-ROM, Power Cord, VGA Computer Input Cable (Dsub15 to Dsub15), Wireless Remote Control (with Lithium battery CR2025).

OPTIONAL ACCESSORIES:

Replacement Lamp, Component Video Input Adapter Cable (Dsub15 to 3RCA), Ceiling Mount, Ceiling Post & Plate, Wall Mount (includes mounting plate, arm and projector mount).

Specifications subject to change without notice. ©2011 Eiki International, Inc. Printed in the USA. 08/15/11



Eiki International, Inc.

30251 Esperanza Δ Rancho Santa Margarita, CA 92688-2130
 Phone: 800-242-3454 Δ Fax: 800-457-3454 Δ E-mail: usa@eiki.com

In Canada: 310 First St.- Unit 2, P.O. Box 156 Δ Midland, ON L4R 4K8
 Phone: 800-563-3454 Δ Fax: 800-567-4069 Δ E-mail: canada@eiki.com