

XGA Mini Projector



LC-XM4

1100 ANSI Lumens!

Get the rich color imaging of 3-panel LCD technology in a very compact and lightweight portable projector.



- Weighs about 6 lbs! Footprint smaller than a sheet of paper.
- 1100 ANSI Lumens, 90% uniformity, and 300:1 contrast ratio.
- 3 panel LCD imaging delivers a rich, color saturated picture.
- True XGA resolution. SXGA, XGA, SVGA, VGA and MAC compatible.
- Quiet operation: fan noise only 37 dBA.
- Anti Keystone image offset. Digital keystone correction.
- Wireless remote control. 4X Digital Zoom, Freeze and No Show.
- Accepts Composite, S-Video and DVD & HDTV Component Video Input.
- Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.
- Soft Carry Bag Included.
- 3 Year* Projector Warranty.

EIKI
PROJECTORS

EIKI Means Projectors ... and more!

LC-XM4



ATA case available.



Soft carry bag included.



Full array of connections:
just connect & project.



Card-style wireless
remote projector control.

INCLUDED ACCESSORIES: Owner's Manual. AC Power Cord. Lens Cover. HD15 (VGA-type) Computer Input Cable. Wireless Remote Projector Control With Battery (Lithium, button type). Soft Carry Bag.


OPTIONAL ACCESSORIES: Replacement Lamp. MAC Adapter. Wireless Remote Control with Mouse and Laser Pointer & Batteries (AAx2). Mouse cables for computer PS/2, Serial, ADB and Ports. 33' (10m) Mouse Extension Cable for Control Port., Soft Carry Bag for Projector and Notebook Computer. Luggage-Style Carrying Case with Wheels, Telescoping Handle, and Detachable Computer Compartment. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate.

SPECIFICATIONS: LC-XM4

Screen Brightness	1100 ANSI Lumens
Illumination Uniformity	90%
Size of Color Palette	16.7 Million
Contrast Ratio	300:1 (Full ON/OFF)
Horizontal Resolution	550 TV Lines
Projection Lamp	150 Watt UHP
Estimated Lamp Life	2,000 Hrs.
Imaging System	0.7" PolySilicon active matrix TFT Panels x 3
Screen Pixels	1024 x 758 in stripe configuration
Total Pixels	2,359,296 (1024 x 768) x 3
Lens Type	Manual Zoom and Focus
Lens Specs	Speed: f:1.6~1.78; FL: 1.13~1.36 in. (28.7~34.5 mm)
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width: 2.02~2.4
Image Diagonal	34~200 in. (86.4~508 cm)
Image Width	2.3~13.3 ft. (0.7~4.07 m.)
Throw Distance	4.6~32 ft. (1.4~9.75 m.)
Front Elevation / Maximum Pitch	up to 10.6° up / +/-20°
Anti Keystone	Optical: Fixed Offset (Top:Bottom) Ratio 19:1
Keystone Correction	Digital: Variable Adjustment +20° ~ -20°
Scanning Frequency	Auto: H Sync. 15-100kHz; V Sync. 50-100Hz
Dot Clock	140 MHz
Image Orientation	Normal, Reversed, Inverted
Local Control / Power Management	Full Function/Auto Shut-Off
Remote Proj & Mouse Ctrl	Infra Red x 1
Control Port	USB x 1 (Mouse), Mini DIN 8 Pin x 1 (Mouse & RS-232)
Computer Native Resolution	1024 x 768 (XGA)
Computer: Compatibility	SXGA, XGA, SVGA, VGA & MAC
Computer: Formats	1280x1024, 1024x768, 800x600, 640x480
Computer: Image Sizing	Normal, or Smart Compressed or Expanded
Computer: Lower Resolutions	Displayed normal or Smart Expanded
Computer: Channels	1
Computer: Inputs	HD15 x 1
Computer: Audio In	Stereo: MiniStereo x 1
Video: Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N
Video: Formats Supported	Normal 4:3 and Wide Screen 16:9
Video: Image Sizing	Video Scaling Technology
Video: Channels	1
Video: In	RCA x3 (Composite/Component: Y,Pb/Cb,Pr/Cr) S-Video x1
Video: HDTV Standards Supported	1080i, 1035i, 720p, 575i/p, 480i/p
Video: Audio: Input	Stereo: MiniStereo x 1
Audio: Amplifier	Mono: 1 Watt RMS
Audio: Built In Speaker	Mono: 1.1 (2.8 cm) x 1
Audio: Speaker Output	Stereo: MiniStereo x 1
Fan Noise	37 dBA
Cabinet Size** (HxWxD)	3.0 x 10.2 x 9.1 in. (75.8 x 257 x 230 mm.)
Extremities (Additional):	(H) Leg: 0.6 in. (14.9 mm.)
Weight	6.18 lbs. (2.8 kg.)
Packaged Size (HxWxD)	12.3 x 14.8 x 14.0 in. (312 x 374 x 355 mm.)
Packaged Weight	14.1 lbs. (6.4 kg.)
Power Requirements	100-240V AC, 50/60Hz
Power Consumption / Heat	250 W / 854 BTU/hr (215 Kcal/hr)
Power Cord	10' (3M) Type 3, Detachable
Safety Compliance	UL Listed
Operating Temperature	41~95°F (5~35°C)
User Maintenance	Clean Air Filter, Replace Lamp
Security Facilities	Kensington® Security Slot
Warranty: Projector	3 Yr. / 6000 Hr.* (Parts & Labor to Correct Defects)
Warranty: Lamp	90 Days (Failed Lamp Replaced Pro-Rata)

* Whichever occurs first

Talk to your EIKI Dealer... the "pro" in projection.



Specifications subject to change without notice.
©2002 EIKI International, Inc. Printed in the USA. 07/15/02

Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130
Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8
Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

Fax-on-Demand: (Toll Free) 877-345-4329 <http://www.eiki.com>