

Now with 1 Year Lamp
and Air Filter Warranties.**

LC-XS25

XGA "School" Series
2600 ANSI Lumens

Get the rich color imaging of 3-panel LCD technology in a quiet, bright classroom projector requiring dramatically reduced maintenance.

- ▼ 2600 ANSI Lumens, 85% uniformity, and 450:1 contrast ratio.
- ▼ 3 panel LCD imaging delivers a rich, color saturated picture.
- ▼ XGA resolution. WXGA and UXGA-VGA and MAC compatible.
- ▼ Top cabinet lamp access. Transparent, permanent lens cover.
- ▼ 7-Watt audio system. Long life, self-advancing air filter cartridge.
- ▼ Closed Caption decoding. Built-in security bar. Auto Setup.
- ▼ Quiet operation: fan noise as low as 27.5 dBA.
- ▼ Smart data compression/expansion, and video scaling.
- ▼ Convenient mid-range 1.2:1 manual zoom and focus lens.
- ▼ Preset image offset. Vertical digital keystone correction.
- ▼ Accepts Composite, Component and S-Video in all major standards.
- ▼ Displays both 4:3 and 16:9 formats. Supports most HDTV resolutions.
- ▼ Converts Interlace to Progressive scan. 3-2/2-2 Pulldown support.
- ▼ Variable Power Management option. Optional local or remote keylock.
- ▼ Custom warm-up screen option. Green chalkboard projection mode.
- ▼ Wireless remote control. Digital Zoom 50-400%. Turn OFF and Go!
- ▼ 3 Year* Projector Warranty!



New Features:

1. Big Sound: 7 Watt RMS Audio System.
2. Closed Captioned Support: (NTSC Composite or S-Video).
3. More Security: Built-in security bar, and key and projector lock features.

Reduced Maintenance:

4. Better Cooling: sealed lens housing assures one-way filtered airflow.
5. Reduced Maintenance: up to 3000 hour self-advancing cartridge air filter.
6. Easy Lamp and Air Filter Change: access is from the top of the projector.

EIKI
Projectors... and more!

LC-XS25 2600 ANSI Lumens

SPECIFICATIONS:

Screen Brightness	up to 2600 ANSI Lumens
Illumination Uniformity	85%
Color Reproduction	8-bit/16.7 Million Colors
Contrast Ratio	450:1 (Lamp Mode: Auto; Image Mode: Dynamic)
Projection Lamp	220 Watt UHP
Estimated Lamp Life	up to 3000 Hours of Use
Imaging System	0.63" PolySilicon active matrix TFT Panels x 3
Screen Pixels	1024 x 768 in stripe configuration
Total Pixels	2,359,296 ((1024 x 768) x 3)
Lens Type	Manual Zoom and Focus
Lens Specs	Speed: f:1.6~1.76; FL: 0.879~1.055 in. (22.33~26.80 mm)
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width: 1.72~2.07:1
Image Diagonal	40~300 in. (102~762 cm)
Image Width	2.67~20 ft. (0.84~6.1 m)
Throw Distance (Wide-Tele)	4.6~41.6 ft. (1.4~12.7 m)
Front Elevation/Maximum Pitch	up to 10° up/up to 10° up or down
Anti Keystone	Fixed Image Offset, Ratio (Top:Bottom) 9:1
Vertical Keystone Correction	Digital: up to 20° up or down
Scanning Frequency	Auto: H Sync. 15-100kHz; V Sync. 50-100Hz
Dot Clock	140 MHz
Image Orientation	Normal, Reversed, Inverted
Local Control/Power Management	Full Function/Auto Shutdown
Remote Projector Control	Wireless (Infra Red) x 1
Control Port (for RS-232 control)	Dsub 9 pin x 1
Computer Native Resolution	1024 x 768 (XGA)
Computer: Compatibility	UXGA (analog only) SXGA+, SXGA, WXGA, XGA, SVGA, VGA & MAC
Computer: Formats	1600 x 1200 through 640 x 480
Computer: Higher Resolutions	Displayed panned or Smart Compressed
Computer: Lower Resolutions	Displayed normal or Smart Expanded
Video Compatibility	NTSC/PAL/SECAM/NTSC 4.43/PAL-M&N
Video HD Compatibility	480i/p, 575i/p, 720p, 1035i, 1080i
Video Formats Supported	Normal 4:3 and Wide Screen 16:9
Video: Image Sizing	Video Scaling Technology
Image Signal Inputs	
Computer in 1: Analog** or Digital, or Digital Video w/HDCP:	DVH x 1
Computer in 2: Analog/Component Video***:	Dsub15 x 1
Video In:	RCA x 1 (Composite) and S-Video x 1 (Y/C)
Audio Signal Inputs	
Computer 1 & 2/Component	Stereo: MiniStereo x 2
Composite/S-Video	RCA x 2 (L & R)
Outputs:	
Computer Monitor:	Dsub15 x 1
Audio Output	Stereo: MiniStereo x 1 (Variable)
Audio: Amplifier	Mono: 7 Watts RMS
Audio: Built In Speaker	1.46 in. (3.7 cm) x 1 (Mono)
Fan Noise	as low as 27.5 dBA
Cabinet Size (HxWxD)**:	3.3 x 16.1 x 10.3 in. (85.0 x 410 x 262.8 mm)
Weight	8.82 lbs. (4.0 kg)
Packaged Size (HxWxD)	9.2 x 20.3 x 17.3 in. (233 x 516 x 440 mm)
Packaged Weight	14.55 lbs. (6.6 kg)
Power Requirements	100-240V AC, 50/60Hz
Power Consumption	up to 304 Watts
Heat	up to 1,037 BTU (261 KC)
Power Cord	10' (3M) Type 3, Detachable
Electrical Safety Compliance	UL, cUL, IEC
Electromagnetic Compatibility	FCC Class B, CE Mark
Security Facilities	Kensington® Security Slot, Security Bar
Operating Temperature	41~95°F (5~35°C)
User Maintenance	Replace Air Filter Cartridge, Replace Lamp
Warranty: (to the original end-use customer)	
Projector:	3 Years/6000 Hour Use* (Parts/Labor to Correct Defects)
Lamp and Air Filter:	1 Year/2000 Hours Use** (replaced Pro Rata)

*/** Note: whichever occurs first



LC-XS25 - XGA "School" Series Projector.




Replaceable air filter cartridge.



Just connect, and project.



Local control.



Remote control.

Talk to your EIKI Dealer... the "pro" in projectors.



Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130

Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8

Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

<http://www.eiki.com>

INCLUDED ACCESSORIES:

Quick Start Guide. Owner's Manual on CD-ROM. AC Power Cord. VGA-type Computer Input Cable (D-sub15). Wireless Remote Control & Batteries (AA x 2).

OPTIONAL ACCESSORIES:

Replacement Lamp. Replacement Air Filter Cartridge. Soft Carry Bag. Computer In 1 "VGA" (Analog) Input Cable** (DVH~D-sub15). Computer In 2 Component Video Input Cable*** (D-sub15~3-RCA). Ceiling Mount. Ceiling Post and Plate.

EIKI
Projectors... and more!

Specifications subject to change without notice.
©2009 EIKI International, Inc. Printed in the USA. 01/15/09