

LC-XT9 9000 ANSI lumens

Get the rich color imaging of 3 panel LCD technology in a configurable projector with remarkable brightness and contrast.



Shown with optional lens.

XGA "Theater" Projector

- ❑ 9,000 ANSI Lumens bright at 90% uniformity and a 1100:1 contrast ratio.
- ❑ Native XGA. Compatible with UXGA through VGA. WXGA compatible. Video scaling.
- ❑ Works on 120V AC power (15 amp circuit). No special wiring required!
- ❑ Projects images up to 40' wide (600" diagonal). (Supplied without lens.)
- ❑ Quick Change Lens installation System. Wide choice of lenses available.
- ❑ Power Lens Shift. Lens can be shifted vertically and horizontally.
- ❑ Accepts most most video signal input, including DVI, RGB, Y/C, DVD, HDTV.
- ❑ Compatible with 480i/p, 575i/p, 720p, 1035i, 1080i - 50/60 input resolutions.
- ❑ Displays video 4:3 & 16:9 in NTSC, PAL/SECAM/NTSC 4.43/PAL-M/PAL-N.
- ❑ DVI input supports HDCP for true digital imaging. 2-3 pulldown support.
- ❑ 4 input bays. Interchangeable input modules permit reconfiguration.
- ❑ Supplied software permits the preconfiguring of color adjustments.
- ❑ Wireless/wired remote control. Digital Zoom 50%~700% (horizontal).
- ❑ Capable of extended operation (up to 23 hours/day) with regular maintenance.
- ❑ 3 Year* Projector Warranty!


Outstanding Features

1. Bright yet economical. 9,000 ANSI Lumens.
2. Delivers an impressive 1100:1 contrast ratio.
3. Optical imaging engine optimized for extended use.
4. Works on 120V/15 amp circuit. No special wiring

EIKI
Projectors... and more!



Shown with optional lens.



Hg Lamp Contains Mercury. Do not put in trash. Dispose-of-as Hazardous Waste, according to the laws in your jurisdiction.



INCLUDED ACCESSORIES:

Quick Start Guide. Owner's Manual on CD-ROM. AC Power Cord. Computer Input Cable 6' (1.8m) HD15~HD15. Wireless/wired Remote Control & 2 AA batteries. Lens Aperture Cover. Color Management Software. Lens Mount Adapter x 2.

OPTIONAL ACCESSORIES:

Telephoto, Midrange and Wideangle Lenses. Replacement Lamps. Additional DVI, 5 BNC and PC Input Modules. Y/C (BNC x 2/ S-Video) Input Modules. DVH w/HDCP (Digital Video) Input Module. Dual (HD and SD) SDI Input Module. HD-SDI Input Module. Upconverter Input Module. Network Control Module. Hard Shipping Case with wheels and telescoping handle. Ceiling Mount and Post & Plate. EZ-250 Local Control. NPC-1 Network Control.

EIKI

Projectors... and more!

Specifications subject to change without notice.
©2007 EIKI International, Inc. Printed in the USA. 03/01/07

SPECIFICATIONS: LC-XT9

Brightness up to 9000 ANSI Lumens (measured with AH-22051 lens)
 Uniformity 90%
 Size of Color Palette 16.7 Million
 Contrast Ratio 1100:1 (Typical: lamp control mode "Auto")
 Horizontal Resolution 800 TV Lines (HDTV)
 Projection Lamp 250 Watt UHP x 4
 Estimated Lamp Life Up to 2000 Hours
 Imaging System 1.8" PolySilicon active matrix TFT Panels x 3
 Screen Pixels 1024 x 768 in stripe configuration
 Total Pixels 2,359,296 ((1024 x 768) x 3)
 Lens Not Included
 Image Diagonal 40~600 in. (101.6~1524 cm.)
 Image Width 2.67~40 ft. (0.82~12.2 m.)
 Throw Distance See specifications of selected lens
 Front Elevation Up to 5.7° up
 Vertical Anti-Keystone Power Lens Shift, Ratio (max) (T:B) 10:0~0:10
 Horizontal Anti-Keystone Power Lens Shift, Ratio (max) (L:R) 3:2~2:3
 Vertical Keystone Correction Digital: Variable Adjustment +40°~ -40°
 Scanning Frequency Auto: H Sync. 15-120kHz; V Sync. 50-120 Hz
 Dot Clock 230 MHz
 Image Orientation Normal, Reversed, Inverted
 Local Control / Power Management Full Function/Auto Lamp Shut-Off
 Remote Projector & Mouse Control Wireless/wired x 1
 Mouse Control Ports (On input modules 1,2 & 4) Mini DIN x 3, USB x 1
 Wired Remote Jack MiniStereo x 1
 RS-232 Control Port (In & Out) Dsub9 x 2
 Computer Native Resolution 1024 x 768 (XGA)
 Computer Compatibility UXGA & SXGA+


SXGA, WXGA, XGA, SVGA, VGA and MAC
 Computer: Image Sizing Normal or Smart compressed or expanded
 Video: Standards NTSC/PAL/SECAM/NTSC 4.43/PAL-M/PAL-N
 Video: Formats Supported Normal 4:3 and Widescreen 16:9
 Video: Image Sizing Progressive Video Scaling
 Video: Systems Composite, Component, S-Video
 Video Compatibility 480i/p, 575i/p, 720p, 1035i, 1080i-50/60
 Input Modules: Interchangeable: standard configuration below

- Image Signal Inputs:
1. DVI DVH x 1 data/video, RCA x 2 audio, 8-pin DIN x 1 control (provides DVI digital data, HD15 analog data via optional adapter, and DVI w/HDCP digital video)
 2. RGB/DVD/HD BNC x 5 video, RCA x 2 audio, 8-pin DIN x 1 control (RGB G-sync, RGB H+V, RGBHV, Component and Y, Pb/Cb, Pr/Cr)
 3. PC HD15 x 1 data, RCA x 2 audio, 8-pin DIN x 1 control
 4. Blank

Audio : Output - Line (Stereo) RCA x 2 (L&R)
 Fan Noise as low as 51 dBA
 Cabinet Size (H x W x D) 10 x 22.9 x 30.9 in. (252 x 581 x 783 mm.)
 Weight 80.5 lb. (36.5 kg.)
 Packaged Size (H x W x D) 26.1 x 34.7 x 48.4 in. (662 x 880 x 1228 mm.)
 Packaged Weight 109.1 lb. (49.5 kg.)
 Power Requirements 100~120/200~240V AC, 50/60Hz
 Power Consumption / Heat up to 1500 Watts/5118 BTU (1290 KC)
 Power Cord 10' (3 M) Type 3, Detachable
 Safety Compliance UL Listed
 Operating Temperature 41~95°F (5~35°C)
 User Maintenance Clean Air Filter, Replace Lamp

Warranty: (to the original end-use customer)
 Projector 3 Yr./6000 Hours Use* (Parts/Labor to Correct Defects)
 Warranty: Lamp 90 Days (Failed Lamp Replaced Pro-Rata)
 * whichever occurs first

Talk to your EIKI Dealer... the "pro" in projectors.



Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130
 Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com
 In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8
 Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

<http://www.eiki.com>