

**G SERIES Projectors (LC-XG210/200 & LC-XG110/100)**

Resolution: XGA (1024x768)

Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)

True Aperture: 0.792 in. wide

**Screen Dimensions (H & W in ft., D in in.).**

H'	1.5	3	5	6	7.5	9	12	15
W'	2	4	6.67	8	10	12	16	20
D"	30	60	100	120	150	180	240	300

EIKI Part No.	Ref.	T/W	Shift/Limits	Standard Lens	EFL	Distance (expressed in feet).							
Standard Lens		1.69	10:0~1:1	1.34"~1.73" Power, Zoom (34~44 mm) f:1.7~2.1	1.34	3.4	6.8	11.3	13.5	16.9	20.3	27.1	33.8
		2.18			1.73	4.4	8.7	14.6	17.5	21.8	26.2	-	-

EIKI P/N		T/W		Auxiliary Lenses	EFL	Distance (expressed in feet).							
0001-4298	1625	0.79	1:1 (On Axis)	0.629" Manual, Fixed (16 mm) f:2.5	0.629	1.6	3.2	5.3	6.4	7.9	9.5	12.7	15.9

0001-4300	2125	1.04	1:1 (On Axis)	0.826" Manual, Fixed (21 mm) f:2.5	0.826	2.1	4.2	7	8.3	10.4	12.5	16.7	20.9

0001-4264	1028	1.26	8:1~1:1	1.0" Manual, Fixed (25.4 mm) f:2.8	1.00	2.5	5.1	8.4	10.1	12.6	15.2	20.2	25.3

AH-23511	W10	1.26	10:0~1:1	1.0"~1.3" Power, Zoom (25.4~33.0 mm) f:2.3~2.6	1.00	2.5	5.1	8.4	10.1	12.6	15.2	20.2	25.3
		1.64			1.30	3.3	6.6	10.9	13.1	16.4	19.7	-	-

AH-23541	T10	2.16	10:0~1:1	1.71"~2.74" Power, Zoom (43.43~69.49 mm) f:2.0~2.6	1.71	4.3	8.6	14.4	17.3	21.6	25.9	34.5	43.2
		3.46			2.74	6.9	13.8	23.1	27.7	34.6	-	-	-

0001-4269	275	2.49	10:0~1:1	1.97~2.76" Manual, Zoom (50~70 mm) f:2.5	1.97	5.0	9.9	16.6	19.9	24.9	29.8	39.8	49.7
		3.48			2.76	7.0	13.9	23.2	27.9	34.8	41.8	55.8	69.7

0001-4266	500	3.47	10:0~1:1	2.75"~5.00" Manual, Zoom (70~120 mm) f:2.8	2.75	6.9	13.9	23.2	27.8	34.7	41.7	55.6	69.4
		6.31			5.00	12.6	25.3	42.1	50.5	63.1	75.8	101	126

0001-4267	087	6.57	10:0~1:1	5.2"~8.7" Manual, Zoom (132~220 mm) f:3.0	5.20	13.1	26.3	43.8	52.5	65.7	78.8	105.1	131.3
		10.98			8.70	22.0	43.9	73.3	87.9	110	131.8	175.8	219.7

0001-4268	900	7.58	10:0~1:1	6.00"~9.00" Manual, Zoom (152~229 mm) f:3.5	6.00	15.2	30.3	50.5	60.6	75.8	90.9	121.2	151.5
		11.36			9.00	22.7	45.5	75.8	90.9	113.6	136.4	181.8	227

**Notes:**

<b>Image Height for 16:9:</b> width stays the same as 4:3 (ignore Diagonal)	<b>H'</b>	1.13	2.25	3.75	4.50	5.63	6.75	9.00	11.25
---	-----------	------	------	------	------	------	------	------	-------

**How to use the T/W column.** If your screen size does not appear on this chart, use the T/W column to find the lens you need.

Divide the Throw distance by the screen Width to get your "target T/W number". Then, look for a lens with a T/W range that covers it.

**Understanding Shift/Limits.** The numbers in the Shift/Limits column express the projector positions possible as a ratio of the image heights Above:Below a line drawn perpendicular to the screen between the lens and the screen. 1:1 = center of the image. 10:0 = top of the image.

**These charts are a simulation.** Effective Focal Length (EFL) most accurately represents lens behavior, and drives the calculations..

Calculations are from the front glass of the lens and accurate to approximately +/- 3%. Specifications are subject to change without notice.

Eiki International, Inc. Tel: 800-322-3454, Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada: Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com

Website: <http://www.eiki.com>

