

EIKI 5030A

Projectors... and more!

KEY FEATURES

Powerful room filling sound.

Maximum strength, minimum weight. Eiki's incredibly durable high-impact ABS body is built to endure years of punishment.

Comfortable, full-size controls: Play, record, fast rewind, fast forward/cue, pause and stop/eject keys. Braille raised symbols on keyboard for the vision impaired.

Side-mounted listening center jacks allow private listening for up to 7 people with headsets.

Built-in electret condenser microphone with automatic and manual recording level controls.

Automatic Tape Stop and power shut-off in all modes.

Standard 1/4" monaural audio jacks for headset and speaker output.


2X digital tape counter with reset buttons.

Full Range Volume and Tone Controls.

Pop-Up Cassette Lid automatically lifts cassette up for quick tape changes.

Dependable Cassette Tape transport mechanism.

AUDIO TAPE RECORDER /PLAYER



5030A

OPTIONAL ACCESSORIES

Standard headset Remote control microphone

Specifications

| Frequency Response | 125Hz to 8KHz | Auxilary Input Jack | 1/8" (3.5 mm) x 1 |
|---|--|---|-----------------------------|
| Wow & Flutter | 0.17% | Remote Pause | 1/10" (2.46 mm) x 1 |
| Tape Speed | 1 7/8 inches per second | Headset Jacks | 1⁄4" x 7 |
| Tape Capacity | C30, C-60, C-90 | Audio Output: Amplifier | 10 Watts RMS (D.H.T. 10%) |
| Rewind Time | C-60 1 minute, 50 seconds | Signal To Noise Ratio | 45dB |
| Heads Record, | Record, playback and erase | Audio: Output Speakers | 10 x 13cm (5" round x 1) |
| Battery or AC Operation | AC only | Speaker Jacks | 1/4", 4 Ohm x 1 |
| Tape Format | Cassette, monaural | Dimensions (H x W x D) | 330 x 241 x 101 mm |
| Tape Counter | Resettabble 3-digit (ANSI 2x standard) | Weight | 2.78 kg (without batteries) |
| Operating Keys Record, play, review, cue/fast forward, pause, stop, eject | | Packaged Weight | 3.63 kg (without batteries) |
| Record Level Indicators | ALC LED meter | Power Requirements | AC only, 120 Volts, 60 Hz |
| Record Level Control | ALC on-off switch | Power Consumption | 18 W approximately |
| Microphone Electret condenser, omni directional monamural type | | Safety Compliance | cUL Listed |
| Remote Microphone Jack | 1/8" (3.5 mm) x 1 | Warranty - Unit 1- Year limited qarranty from date of original purchase for | |

Specifications subject to change without notice. ©2002 Eiki International, Inc. Issued June 12, 2001.

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: infocanada@eiki.com Fax-on-Demand: (Toll Free) 877-345-4329 Visit our World Wide Web site: http://www.eiki.com