

Projectors... and More!

EIP-WX5000

5,200 ANSI lumens bright with 90% uniformity and a 1800:1 contrast ratio. Native WXGA resolution. Compatible with inputs up-to UXGA and WXGA. Supports analog and digital video input in all color standards up-to 1080p. 3 chip DLP® imaging technology delivers a "seamless," high-contrast image. Dual lamp system provides redundancy and permits 4 brightness levels. Power zoom and focus lens. Optional wide-angle and telephoto lenses. Vertical and horizontal power lens shift and digital keystone correction. Unique Projector Stack Control and VideoWall signal division features. Accepts composite, component, and S-Video in all major standards. Built-in wired LAN connection for projector monitoring and control. Variable power management option. Custom warm-up screen option. Wireless/wired remote with remote mouse control. Mechanical shutter for true black screen in "No Show" mode. Kensington® security slot. Local or remote keylock functions. 3 year projector warranty.

EIP-WX5000

5,200 ANSI Lumens / WXGA / 3-chip DLP® Theater Series Projector



EIP-WX5000

Included Accessories: Quick Start Guide, Owner's Manual and CAD Drawings on CD-ROM, Power Cord, Lens Cover, VGA Computer Input Cable (Dsub15 to Dsub15), Wireless/Wired Remote Control (with 2 AA Batteries), Remote Mouse Receiver on USB-A Cable.

Optional Accessories: Replacement Lamps, Wideangle, Midrange and Telephoto Lenses, ATA-Style Shipping Case with Wheels and Telescoping Handle, Ceiling Mount, Ceiling Post & Plate.

SPECIFICATIONS: Model FIP-WX5000

SPECIFICATIONS: Model EIP-WX5000			
Brightness up-to 5,20	0 ANSI Lumens (with standard AH-55501 lens)	Video Input Analog	480i/p, 575i/p, 720p, 1035i, 1080i/p
Contrast Ratio up-to 1800:1		Video Input Digital	480i/p, 575i/p, 720p, 1035i, 1080i/p
Illumination Uniformity (corner to center) 90%		Image Signal Inputs	
Resolution and Aspect Ra	atio WXGA (1280x800), 16:10	1. HDMI	HDMI x 1
Color Reproduction	8-bit (16.7 million colors)	2. DVI-D (w HDCP)	DVI-D x 1
Projection Lamp	280 Watts UHP x 2	Computer / Component	Dsub15 x 1
Estimated Lamp Life	up-to 3,000 Hours	4. Analog	BNC x 5
Imaging System 0.65 in (16.5 mm) DDR 3 DLP® DMD x 3		Component Video (Y, Pb/Cb, Pr/Cr), 3BNC	
Total Pixels	3,072,000 ((1280x800) x 3)	5. S-Video	S-Video x 1
Scanning Frequency	Auto: H: 15-126 kHz; V: 43-200 Hz	6. Composite	RCA x 1
Pixel Clock	up-to 230 MHz	Audio Signal Inputs	
Lens	Changeable - Power Zoom and Focus	For Inputs 2, 3 & 4	Stereo: MiniStereo x 3
Lens Specs	Speed: f: 2.5; FL: 1.00-1.26 in (25.5-32 mm)	For inputs 5 & 6 (2 jacks per	video input) Stereo: RCA x 2
Lens Ratios	Zoom Max:Min: 1.25:1; Throw:Width 1.8-2.3:1	Outputs	• •
Image Diagonal	60-280 in (152-711 cm)	Computer / Component	Dsub15 x 1
Image Width	4.2-19.8 ft (1.3-6.0 m)	Audio Output	Stereo: MiniStereo x 1
Throw Distance (Wide-Tele) 7.9-45 ft (2.4-13.7 m)		Amplifier ·	Stereo: 3 Watt
Projector Elevation Adjustment (legs) up-to 5° Up		Speaker	1.3 x 2.6 in (3.4 x 6.8 cm) x 2 (Stereo)
Maximum Pitch	up-to 9° Up or Down	Fan Noise	as low as 34 dBA
Vertical Lens Shift (% of i	mage height) up-to 66% Up or Down	Cabinet Size (HxWxD) 7	7.5 x 19.7 x 25.1 in (19.0 x 50.0 x 63.7 cm)
Horizontal Lens Shift (% of image width) up-to 35% Left or Right		,	(exlcuding legs)
Vertical Keystone Correct	tion Digital: up-to 40° Up or Down	Weight	58.6 lb (26.6 kg)
Horizontal Keystone Corr	ection Digital: up-to 30° Left or Right	Packaged Size (HxWxD)	15.8 x 28.4 x 34.3 in (40 x 72 x 87 cm)
Image Orientation	Normal, Reversed, Inverted	Packaged Weight	77.2 lb (35 kg)
Local Control / Power Ma	inagement Full Function / Auto Shutdown	Power Requirements	100-240V AC, 50/60 Hz
RS232 Control Port	Dsub9 x 1	Power Consumption	up-to 755 W
Remote Projector Control	Wireless/Wired x 1	Heat .	up-to 2,578 BTU/hr
Wired Remote Control Po	ort Mini-Stereo x 1	Power Cord	6 ft (1.8 m) Type C13, Detachable
LAN Port	RJ45 x 1	Electrical Safety Compliance	ÌEC / UL / cUL
Computer Input in Pixels up-to 1600x1200 (4:3), 1280x800 (16:10)		Electromagnetic Compatibility	FCC Class A, CE Mark
Analog 4x3 Inputs UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC		Security Facilities	Kensington® Security Slot
Analog Wide Inputs WXGA		Operating Temperature	41-104°F (5-40°C)
Digital 4x3 Inputs	SXGA+, SXGA, XGA, SVGA, VGA	User Maintenance	Clean Air Filter, Change Lamps
Digital Wide Inputs WXGA		UPC 4571194672435	
Video Formats NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N L		Limited Warranty: to the original end-use customer only	
Image Signal Resizing	Smart Scaling Technology	Projector	3 years
3 0 0	3 07	Lamp 6 months ownersh	ip / 500 hours use (whichever occurs first)

EIKI® is a registered trademark of Eiki International, Inc. DLP® is a registered trademark of Texas Instruments. HDMI is a registered trademark of HDMI Licensing LLC. Kensington is a registered trademark of ACCO Brands Corporation.