




A-key to better communications.

# LC-SE10

## KEY FEATURES: Model LC-SE10

New! AutoFocus, Auto Keystone, Auto Set Up. New! Variable Audio Out.  
New! Corner Keystone Correction. New! USB Key Lock Security.  
3000 ANSI Lumens, 85% uniformity, and 500:1 contrast ratio.  
3 panel LCD imaging delivers a rich, color saturated picture.  
True SVGA resolution. XGA, SVGA, and VGA compatible.  
Auto Lamp optimizes brightness. Fan noise only 34 dBA in Eco-mode.  
Smart data compression / expansion, and video scaling.  
Power zoom and focus. Vertical and horizontal digital Keystone Correction.  
Wireless remote with mouse and Laser pointer. 7X digital zoom.  
Accepts Composite, S, and Component Video in all major standards.  
Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.  
Optionally converts SDi to SDp. Supports HDTV 720p, 1035i, and 1080i.  
Variable Power Management option. Optional local or remote keylock.  
DVI is HDCP compatible. Slideshow Page Up/Down on remote control.  
Remote Pointer/Spotlight effect. Custom warm-up screen image option.  
3 Year\* Projector Warranty!

## SVGA "Crystal" Series



LC-SE10

**Included Accessories:** Owner's Manual. AC Power Cord. Lens Cover. VGA type Computer Input Cable (HD15 ~ DVI-I).  
Wireless Remote Control With Mouse and Laser Pointer & Batteries (AA x 2). Mouse cable for computer USB Port. Dust Cover.

**Optional Accessories:** Replacement Lamp. USB Security Key. MAC Adapter. MAC Monitor Cable. 9 Pin Serial cable for RS-232 communications.  
Executive Carry Case with Computer Compartment. Luggage-Style ("wheelie") Carrying Case with Wheels, Telescoping Handle, and Detachable  
Computer Compartment. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate. 33' (10m) Extension  
Cable for Control Port. Multi Card Director system supports 1. Computerless Slide Show System. 2. Wired Network Projector Control. 3.  
Wi-Fi Content Delivery and Projector Control System. EZtrol Local Control. NPC-1 Network Control.

## SPECIFICATIONS: Model LC-SE10

Screen Brightness	3000 ANSI Lumens / 2,250 in Eco mode	Computer: Lower Resolution	Displayed normal or Smart Expanded
Illumination Uniformity	85%	Computer Channels	2
Size of Color Palette	16.7 Million	Computer Input 1	DVI-I x 1 (HD15 via supplied Input Cable)
Contrast Ratio	500:1 (Full ON/OFF)	Input 2 / Monitor Out	HD15 x 1
Horizontal Resolution	700 TV Lines	Computer Audio In 1 & 2	Stereo: Ministereo x 2
Projection Lamp	300 Watt NSH (240 Watt in Eco mode)	Video: Compatibility	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N
Estimated Lamp Life	2000 Hours	Video: Formats Supported	Normal 4:3 and Wide Screen 16:9
Imaging System	0.99" PolySilicon active matrix TFT Panels x 3	Video: Image Sizing	Video Scaling Technology
Screen Pixels	800 x 600 in stripe configuration	Video: Channels	1
Total Pixels	1,440,000 (( 800 x 600) x 3)	Video: In	RCA x 3 (Composite/Component: Y,Pb/Cb,Pr/Cr S-Video x 1
Lens Type	Power Zoom and Focus	Video: Audio Inputs	RCA x 2 (L&R)
Lens Specs	Speed: f:1.7~2.1; FL: .1.32~1.70 in. (33.6~43.2mm)	Audio: Amplifier	Mono: 1 Watt RMS
Lens Ratios	Zoom Max:Min: 1.29:1; Throw:Width: 1.67~2.15:1	Audio: Built In Speakers	1.1 in. (28 mm) x 1
Image Diagonal	31~300 in. (78.7~762 cm)	Audio: Output -Variable Audio Out	Stereo: Ministereo x 1
Image Width	2.1~20 ft. (0.64~6.1 m.)	Fan Noise	38 dBA (34 dBA in Eco mode)
Throw Distance	4.3~33.1 ft. (1.3~10.1 m.)	Cabinet Size** (HxWxD)	4.4x 15.35 x 10.91 in. (112 x 390 x 277mm.)
Front Elevation / Maximum Tilt	up to 10.3° up / +/- 20°		** excluding legs and lens
Anti Keystone	Fixed Image Offset, Ratio (Top:Bottom) 9:1	Weight	12.8 lbs. (5.8 kg)
Vertical Keystone Correction	Digital: up to 40° up or down	Packaged Size (H x W x D)	13.3 x 24.7 x 18.0in. (337 x 626 x 456mm.)
Horizontal Keystone Correction	Digital: up to 20° left or right	Packaged Weight	21.2 lb (9.6 kg)
Scanning Frequency	Auto: H Sync. 15-80kHz; V Sync. 50-100Hz	Power Requirements	100-240V AC, 50/60Hz
Dot Clock	100 MHz	Power Consumption / Heat	400 W / 1365 BTU/hr (344 Kcal/hr)
Image Orientation	Normal, Reversed, Inverted	Power Consumption / Heat - Eco	320 W / 1092 BTU/hr (275 Kcal/hr)
Local Control / Power Management	Full Function / Auto Shut-Off	Power Cord	10' (3M) Type 3, Detachable
Remote Proj & Mouse Ctrl	Wireless (Infra Red) with Laser Pointer x 1	Safety Compliance	UL Listed
Mouse Port	USB x 1	Security Facilities	Kensington® Security Slot
Service Port	Mini DIN 8 Pin x 1	Operating Temperature	41~95°F (5~35°C)
Computer Native Resolution	800 x 600 (SVGA)	User Maintenance	Clean Air Filter, Replace Lamp
Computer: Compatibility	XGA, SVGA, VGA	Warranty: Projector	3 Yr. / 6000 Hr. *(Parts & Labor to Correct Defects)
Computer: Formats	1024 x 768, 800 x 600, 640x480	Warranty: Lamp	90 Days (Failed Lamp Replaced Pro-Rata
Computer: Higher Resolutions	Displayed panned or Smart Compressed		* Whichever occurs first

**Caution! Laser Radiation – Do not stare into beam. Max. Output: 1 mW. Wave Length: 650 +/- 20 nm. Class II Laser Product.**

**Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.**

Specifications subject to change without notice. ©2003 Eiki International, Inc. Issued December 1, 2003.

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: infocanada@eiki.com

Fax-on-Demand: (Toll Free) 877-345-4329 Visit our World Wide Web site: <http://www.eiki.com>