


LC-XNB4

XGA Notebook Projector

KEY FEATURES: Model LC-XNB4

Weighs less than 9 lbs! Footprint similar to a legal notepad! 1700 ANSI Lumens, 85% uniformity, and 350:1 contrast ratio. 3 panel LCD imaging delivers a rich, color saturated picture. True XGA resolution. SXGA, XGA, SVGA, and VGA compatible. Quiet operation: fan noise as low as 37 dBA. Smart data compression / expansion, and video scaling. Power zoom and focus. Digital keystone correction. Wireless remote with mouse and Laser pointer. 7X digital zoom. Accepts Composite, S, and Component Video in all major standards. Displays both Regular 4:3 and Widescreen 16:9 ratio video formats. Supports HDTV Input at 480i/p, 575i/p, 720p, 1035i, and 1080i. 3 Year* Projector Warranty!



LC-XNB4

Included Accessories: Owner's Manual. AC Power Cord. Lens Cover. HD15 (VGA-type) Computer Input Cable with DVI-I ~ HD15 Adapter. Wireless Remote Control With Mouse and Laser Pointer & Batteries (AA x 2). Mouse cable for computer PS/2 Port. Soft Carry Bag.

Optional Accessories: Replacement Lamp. MAC Adapter. MAC Monitor Cable. 9 Pin Serial cable for mouse and RS-232 communications. Mouse cable for ADB port. Executive Carry Case with Computer Compartment. Luggage-Style ("wheelie") Carrying Case with Wheels, Telescoping Handle, and Detachable Computer Compartment. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate. 33' (10m) Mouse Extension Cable for Control Port. Media Card Imager (Compact Flash Computerless Slide Show System). Wireless Imager (Wi-Fi Content Delivery and Projector Control System).

SPECIFICATIONS: Model LC-XNB4

Screen Brightness 1700 ANSI Lumens Illumination Uniformity 85% Size of Color Palette 16.7 Million 350:1 (Full ON/OFF) Contrast Ratio Horizontal Resolution 800 TV Lines Projection Lamp 200 Watt UHP Estimated Lamp Life 2000 Hours Imaging System 0.9" PolySilicon active matrix TFT Panels x 3 Screen Pixels 1024 x 768 in stripe configuration Total Pixels 2,359,296 ((1024 x 768) x 3) Lens Type Power Zoom and Focus Speed: f:1.7~2.0; FL: 1.47~1.9 in. (37.4~48.3 mm) Lens Specs Lens Ratios Zoom Max:Min: 1.3:1; Throw:Width: 2.02~2.61:1 Image Diagonal 31~300 in. (78.74~762 cm) Image Width 2~20 ft. (0.6~6.1 m.) Throw Distance 5.4~52.2 ft. (1.65~15.91 m.) Front Elevation / Maximum Tilt up to 15.6° up / +/- 20° Anti Keystone Fixed Image Offset, Ratio (Top:Bottom) 9:1 Digital: up to 20° up or down Vertical Keystone Correction Digital: up to 10° left or right Horizontal Keystone Correction Scanning Frequency Auto: H Sync. 15-100kHz; V Sync. 50-100Hz Dot Clock 140 MHz Image Orientation Normal, Reversed, Inverted Local Control / Power Management Full Function / Auto Shut-Off Remote Proj & Mouse Ctrl Wireless (Infra Red) with Laser Pointer x 1 Control Port (Mouse / RS-232) USB x 1, Mini DIN 8 Pin x 1 **Computer Native Resolution** 1024 x 768 (XGA) Computer: Compatibility SXGA, ~ VGA Computer: Formats 1280x1024, ~ 640x480 Computer: Higher Resolutions Displayed panned or Smart Compressed Computer: Lower Resolution Displayed normal or Smart Expanded Computer: Channels 1 Computer: Inputs DVI-I x1 (HD15 via Cable with Adapter) Stereo: MiniStereo x 1 Computer: Audio In Computer: Monitor Out HD15 x 1 Video: Compatibility NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N Video: Formats Supported Normal 4:3 and Wide Screen 16:9 Video: Image Sizing Video Scaling Technology Video: Channels Video: InRCA x 3 (Composite/Component: Y,Pb/Cb,Pr/Cr) S-Video x 1 Video: Audio: Input RCA x 2 (L&R) Audio: Amplifier Mono: 1 Watts RMS Audio: Built In Speakers 1.58 x 1.18 in. (4x3cm) x 1 Audio: Line Output RCA x 2 (L&R) Fan Noise 37 dBA Cabinet Size**(HxWxD) 3.52 x 13.11 x 9.25 in. (89.5 x 333 x 235 mm.) ** excluding foot Weight 8.6 lbs. (3.9 kg) Packaged Size (H x W x D) 15 x 18 x 14 in. (379 x 457 x 356 mm) Packaged Weight 18.52 lb (8.4 ka) Power Requirements 100-240V AC, 50/60Hz Power Consumption / Heat 300 W / 1024 BTU/hr (258 Kcal/hr) Power Cord 10' (3M) Type 3, Detachable Safety Compliance UL Listed Security Facilities Kensington® Security Slot 41~95°F (5~35°C) **Operating Temperature** User Maintenance Clean Air Filter, Replace Lamp Warranty: Projector 3 Yr. / 6000 Hr. *(Parts & Labor to Correct Defects) Warranty: Lamp 90 Days (Failed Lamp Replaced Pro-Rata * Whichever occurs first

This warning is required by the US FDA and pertains to the laser pointer in the wireless remote control of this projector. Caution! Laser Radiation – Do not stare into beam. Max. Output: 1 mW. Wave Length: 650 +/- 20 nm. Class II Laser Product.

Specifications subject to change without notice. ©2002 Eiki International, Inc. Issued June 12, 2001. Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: infocanada@eiki.com Fax-on-Demand: (Toll Free) 877-345-4329 Visit our World Wide Web site: http://www.eiki.com