

Model 392 Overhead Projector

KEY FEATURES:

Economical: designed expressly for school budgets

Durable Construction: heavy duty metal tub Bright, Sharp Image: EYB lamp, efficient optics

Folding Post: move the head out of view when not in use

Wideangle Lens: minimal throw distance required Built-in Lamp Changer: for uninterrupted presentations

Built-in Handles & Cord Storage: move it easily

3 Year Projector Warranty

INCLUDED ACCESSORIES:

Owner's Manual

OPTIONAL ACCESSORIES:

Replacement Lamp Roll-Feed Attachment

SPECIFICATIONS:

Brightness: 2000 Lumens
Projection Lamp: EYB (82V, 360W)
On/Off Control: front-mounted rocker switch
Lamp Changer Control: front-mounted rotating knob
Focus Mechanism: rack and pinion
Lens Type: 1-element open-head
Lens Focal Length: 11.22 in. (285 mm.)

Image Width: 2~20 ft. (0.6~6.1 m.)
Throw Distance: 4.5~8.0 ft. (1.35~2.44 m.)

Screen Size: 48 x 48 ~ 84 x 84 in. (1.2 x 1.2 ~ 2.2 x 2.2 m.)
Cabinet Dimensions: 9.3 x 12.25 x 12.25 in. (24 x 31 x 31 cm.)

Overall Dimensions:

Height (to maximum mirror height & opening): 32.25 in. (82 cm.)
Width (including post): 14.0 in. (36 cm.)

Depth (inc. cord storage & lamp change knob): 14.5 in. (37 cm.)

Folded Dimensions: 12.3 x 14.0 x 18.75 in (32 x 36 x 48 cm.)

Packaged Size: 18.9 x 18.1 x 12.2 in. (48 x 46 x 31 cm)

Packaged Weight: 19.4 lb (8.8 kg)

Power Requirements: 120 VAC / 60Hz

Power Cord: 10' (3M) Type 3, Attached

Power Cord: 10' (3M) Type 3, Attached Safety Devices: Stage Interlock & Thermal Fuse Safety Compliance: UL Listed

Operating Temperature 41~95°F (5~35°C)

User Maintenance: Cleaning and Lamp Replacement as required Projector Warranty: 3 Years (Parts & Labor to Correct Defects)





