

Attached Lens Projectors

Classroom / Meeting Room							Conference
	Entry Level	Full Featured	Laser Light Source	Short Throw	Ultra Short Throw	Full Featured Laser	
Note: Photos are not sized to scale.		<i>Coming Soon...</i> 					
Model	EK-130U / EK-131W	EK-308UK	C602 / C602S	EK-50LU	EK-65LU	C835 / C735	
Key Features	20,000 Hour Infinity Lamp Technology; Digital input with 2x HDMI port; Corner Keystone Correction; 16W Audio System	Full featured, high brightness portables; Lens shift; Corner keystone and pin cushion & barrel image correction; Network monitoring and control	High brightness and contrast 3LCD Laser Projector; Available in Standard & Short Throw lens; 4K Scaler; Full 360° installation capability	Short Throw 3LCD Laser Projector; 20,000 Hour Laser Light Source; 4K Scaler; 16W Audio System; Network monitoring and control	Ultra Short Throw 3LCD Laser Projector; 20,000 Hour Laser Light Source; 4K Scaler; 16W Audio System; Network monitoring and control	High brightness and contrast 3LCD Laser Projector; Laser Light Source; 4K Scaler; HDBaseT input; Full 360° installation capability	
Display Technology	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	
Price (MSRP)	\$1,725 / \$1,225	\$2,200	\$3,000 / \$3,400	\$3,325	\$3,860	\$6,480 / \$4,025	
Brightness	5,000 lumens	6,000 lumens	6,000 lumens	5,000 lumens	6,500 lumens	C835: 8,300 lumens C735: 7,300 lumens	
Native Resolution	EK-130U: WUXGA (1920x1200) EK-131W: WXGA (1280 x 800)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	
Max. Computer Input	WUXGA	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	
Max. Video Input	1080p	1080p	1080p	1080p	1080p	1080p	
Contrast Ratio	15,000:1	10,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1	
Panel Size (Diagonal)	0.64" inorganic	0.64" inorganic	0.64" inorganic	0.64" inorganic	0.64" inorganic	0.64" inorganic	
Lens Type (Throw: Width)	1.26-2.09:1	1.07-1.75:1	C602: 1.08-1.76:1 C602S: 0.68-0.82:1	0.44:1	0.235:1	1.2-2.0:1	
Image Offset / Lens Shift	Fixed Offset: 8.71:1	Lens Shift: U/D: 45%; L/R: 10%	Lens Shift: Up: 45%	Fixed Offset: 99%	Fixed Offset: 119%	Lens Shift: Up 60%; L/R 29%	
Keystone Correction	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 15°; L/R 15°	U/D 5°; L/R 5°	U/D 30°; L/R 30°	
Inputs	Dsub15 x 1; HDMI x 2; RCA x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 2; HDMI x 2; RCA x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 1; HDMI x 2; USB-A x 1; USB-B x 1; MiniStereo x 1	Dsub15 x 1; HDMI x 2; USB-A x 1; USB-B x 1; MiniStereo x 1	Dsub15 x 1; HDMI x 2; USB-A x 1; USB-B x 1; MiniStereo x 1	Dsub15 x 1; HDMI x 2; HDBaseT RJ45 x 1; USB-A x 1; USB-B x 1; MiniStereo x 1	
Outputs	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1; HDMI x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	
Sound System	16 Watt; 1.4" Speaker x 1	10 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	
Network Control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	
Warranty	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*	
Light Source Life	Up-to 20,000 hours	Up-to 4,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	
Lamp Part Number	23040072	22040015	-	-	-	-	
Fan Noise	As low as 30 dBA	As low as 35 dBA	As low as 29 dBA	As low as 28 dBA	As low as 27 dBA	As low as 29 dBA	
Air Filter	Standard	Standard	Standard	Standard	Standard	Standard	
Maximum Pitch	± 10° U/D	± 30° U/D	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°	
Weight	7.0 lb (3.2 kg)	9.9 lb (4.5 kg)	11.0 lb (5.0 kg)	12.1 lb (5.5 kg)	24.0 lb (11 kg)	17.4 lb (7.9 kg)	
Ceiling Mount PN	0173-4293	0173-4367	0173-4293	0173-4293	0173-4293	0173-4293	

Eiki International, Inc.

22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 · Tel: 800-242-3454 · E-Mail: usa@eiki.com · Website: www.eiki.com

Prices and specifications are subject to change without notice. *Projector Warranty: 3 Years or 6,000 Hours (whichever occurs first). See warranty card for full details.

Conference Room			Theater			
	Standard Lens	Short Throw Lens	Full HD - WUXGA			
Note: Photos are not sized to scale.						
Model	C735P	C735PS	EK-900LU / EK-1000LU	EK-1300LU	V1700	V2000
Key Features	1080p with 4K Enhancement displays double HD resolution; High brightness and contrast 3LCD Fixed Lens Laser Projector; HDBaseT input; Full 360° installation capability	1080p with 4K Enhancement displays double HD resolution; High brightness and contrast 3LCD Short Throw Lens Laser Projector; HDBaseT input; Full 360° installation capability	High performance, low maintenance 3LCD Laser Projector; Blue Laser + Phosphor Light Source; 4K Scaler; HDBaseT input; Filter-less design; Full 360° installation capability;	High performance, low maintenance 3LCD Laser Projector; Blue Laser + Phosphor Light Source; 4K Scaler; HDBaseT input; Filter-less design; Full 360° installation capability;	High Brightness 3LCD Laser projector; 1.0" LCD panels; Blue Laser + Phosphor Light Source; HDBaseT input; 4K Scaler; IP6X compliant sealed optical engine; Full 360° installation capability	High Brightness 3LCD Laser projector; 1.0" LCD panels; Blue Laser + Phosphor Light Source; HDBaseT input; 4K Scaler; IP6X compliant sealed optical engine; Full 360° installation capability
Display Technology	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD
Price (MSRP)	\$5,050	\$5,750	\$10,150 / \$12,600	\$18,150	\$27,200	\$35,550
Brightness	7,300 lumens	7,300 lumens	9,000 lumens / 10,000 lumens	13,000 lumens	17,000 lumens	20,000 lumens
Native Resolution	1080p with 4K Enhancement	1080p with 4K Enhancement	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)
Max. Computer Input	4K (4096x2160)	4K (4096x2160)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)
Max. Video Input	1080p, 4K UHD, 4K DCI	1080p, 4K UHD, 4K DCI	1080p	1080p	1080p	1080p
Contrast Ratio	5,000,000:1	5,000,000:1	100,000:1	100,000:1	3,000,000:1	3,000,000:1
Panel Size (Diagonal)	0.64" inorganic	0.64" inorganic	0.76" inorganic	0.76" inorganic	1.0" inorganic	1.0" inorganic
Lens Type (Throw: Width)	1.2-2.0:1	0.68-0.82:1	Supplied without lens	Supplied without lens	Supplied without lens	Supplied without lens
Image Offset / Lens Shift	Lens Shift: Up 66%; L/R 29%	Lens Shift: Up 50%; L/R 23%	Lens Shift: U/D +50-10%; L/R 20%	Lens Shift: U/D +50-10%; L/R 20%	Lens Shift: U/D 65%; L/R 25%	Lens Shift: U/D 65%; L/R 25%
Keystone Correction	U/D 30°; L/R 25°	U/D 30°; L/R 25°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°
Inputs	HDMI x 2; HDBaseT RJ45 x 1; USB-A x 2	HDMI x 2; HDBaseT RJ45 x 1; USB-A x 2	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;
Outputs	MiniStereo x 1; SPDIF x 1	MiniStereo x 1; SPDIF x 1	HDMI x 1; Dsub15 x 1; MiniStereo x 1	HDMI x 1; Dsub15 x 1; MiniStereo x 1	HDMI x 1; MiniStereo x 1	HDMI x 1; MiniStereo x 1
Sound System	16 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	-	-	-	-
Network Control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control
Warranty	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*
Light Source Life	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours
Lamp Part Number	-	-	-	-	-	-
Fan Noise	As low as 29 dBa	As low as 29 dBa	As low as 27 dBa	As low as 27 dBa	As low as 40 dBa	As low as 33 dBa
Air Filter	Standard	Standard	-	-	-	-
Maximum Pitch	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°
Weight	17.4 lb (7.9 kg)	17.4 lb (7.9 kg)	52.9 lb (24 kg)	52.9 lb (24 kg)	63.7 lb (28.9 kg)	84.9 lb (38.5 kg)
Ceiling Mount PN	0173-4293	0173-4293	0173-5049	0173-5049	0173-5049	0173-5049