September 2026

Attached Lens Projectors

	Classroom / Meeting Room					Conference
	Entry Level	*Full Featured*	*Laser Light Source*	*Short Throw*	*Ultra Short Throw*	*Full Featured Laser*
Note: Photos are not sized to scale.						
Model	**EK-130U / EK-131W**	**EK-308UK**	**C602 / C602S**	**EK-50LU**	**EK-65LU**	**C835 / C735**
Key Features	20,000 Hour Infinity Lamp Technology; Digital input with 2x HDMI port; Corner Keystone Correction; 16W Audio System	Full featured, high brightness portables; Lens shift; Corner keystone and pin cushion & barrel image correction; Network monitoring and control	High brightness and contrast 3LCD Laser Projector; Available in Standard & Short Throw lens; 4K Scaler; Full 360° installation capability	Short Throw 3LCD Laser Projector; 20,000 Hour Laser Light Source; 4K Scaler; 16W Audio System; Network monitoring and control	Ultra Short Throw 3LCD Laser Projector; 20,000 Hour Laser Light Source; 4K Scaler; 16W Audio System; Network monitoring and control	High brightness and contrast 3LCD Laser Projector; Laser Light Source; 4K Scaler; HDBaseT input; Full 360° installation capability
Display Technology	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD
Price (MSRP)	$1,725 / $1,225	$2,200	$3,000 / $3,400	$3,325	$3,860	$6,480 / $4,025
Brightness	5,000 lumens	6,000 lumens	6,000 lumens	5,000 lumens	6,500 lumens	C835: 8,300 lumens C735: 7,300 lumens
Native Resolution	EK-130U: WUXGA (1920x1200) EK-131W: WXGA (1280 x 800)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)
Max. Computer Input	WUXGA	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)
Max. Video Input	1080p	1080p	1080p	1080p	1080p	1080p
Contrast Ratio	15,000:1	10,000:1	5,000,000:1	5,000,000:1	5,000,000:1	5,000,000:1
Panel Size (Diagonal)	0.64” inorganic	0.64” inorganic	0.64” inorganic	0.64” inorganic	0.64” inorganic	0.64” inorganic
Lens Type (Throw: Width)	1.26-2.09:1	1.07-1.75:1	C602: 1.08-1.76:1 C602S: 0.68-0.82:1	0.44:1	0.235:1	1.2-2.0:1
Image Offset / Lens Shift	Fixed Offset: 8.71:1	Lens Shift: U/D: 45%; L/R: 10%	Lens Shift: Up: 45%	Fixed Offset: 99%	Fixed Offset: 119%	Lens Shift: Up 60%; L/R 29%
Keystone Correction	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 15°; L/R 15°	U/D 5°; L/R 5°	U/D 30°; L/R 30°
Inputs	Dsub15 x 1; HDMI x 2; RCA x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 2; HDMI x 2; RCA x 1; USB-A x 1; USB-B x 1; MiniStereo x 1; RCA (audio) x 2	Dsub15 x 1; HDMI x 2; USB-A x 1; USB-B x 1; MiniStereo x 1	Dsub15 x 1; HDMI x 2; USB-A x 1; USB-B x 1; MiniStereo x 1	Dsub15 x 1; HDMI x 2; USB-A x 1; USB-B x 1; MiniStereo x 1	Dsub15 x 1; HDMI x 2; HDBaseT RJ45 x 1; USB-A x 1; USB-B x 1; MiniStereo x 1
Outputs	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1 (by switching input); MiniStereo x 1	Dsub15 x 1; HDMI x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1	Dsub15 x 1; MiniStereo x 1
Sound System	16 Watt; 1.4” Speaker x 1	10 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1	16 Watt; 1.4” Speaker x 1	16 Watt; 1.4" Speaker x 1	16 Watt; 1.4" Speaker x 1
Network Control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control
Warranty	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*
Light Source Life	Up-to 20,000 hours	Up-to 4,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours
Lamp Part Number	23040072	22040015	-	-	-	-
Fan Noise	As low as 30 dBA	As low as 35 dBA	As low as 29 dBa	As low as 28 dBA	As low as 27 dBa	As low as 29 dBa
Air Filter	Standard	Standard	Standard	Standard	Standard	Standard
Maximum Pitch	± 10° U/D	± 30° U/D	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°
Weight	7.0 lb (3.2 kg)	9.9 lb (4.5 kg)	11.0 lb (5.0 kg)	12.1 lb (5.5 kg)	24.0 lb (11 kg)	17.4 lb (7.9 kg)
Ceiling Mount PN	0173-4293	0173-4367	0173-4293	0173-4293	0173-4293	0173-4293

Eiki International, Inc.
22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 · Tel: 800-242-3454 · E-Mail: usa@eiki.com · Website: www.eiki.com
Prices and specifications are subject to change without notice. *Projector Warranty: 3 Years or 6,000 Hours (whichever occurs first). See warranty card for full details.

4K Enhanced Optional Lens Projectors

September 2026

	Conference	Auditorium	Theater			
	Fixed Lens	*Optional Lens*	*Full HD - WUXGA*			
Note: Photos are not sized to scale.		*~ NEW ~* 				
Model	**C735P / C735PS**	**S1002P**	**EK-900LU / EK-1000LU**	**EK-1300LU**	**V1700**	**V2000**
Key Features	1080p with 4K Enhancement displays double HD resolution; Available in Standard & Short Throw lens; HDBaseT input; Full 360° installation capability	WUXGA with 4K Enhancement displays double HD resolution; High brightness, low maintenance Optional Lens Laser Projector; Filter-less design; Full 360° installation capability	High performance, low maintenance 3LCD Laser Projector; Blue Laser + Phosphor Light Source; 4K Scaler; HDBaseT input; Filter-less design; Full 360° installation capability	High performance, low maintenance 3LCD Laser Projector; Blue Laser + Phosphor Light Source; 4K Scaler; HDBaseT input; Filter-less design; Full 360° installation capability	High Brightness 3LCD Laser projector; 1.0" LCD panels; Blue Laser + Phosphor Light Source; HDBaseT input; 4K Scaler; IP6X compliant sealed optical engine; Full 360° installation capability	High Brightness 3LCD Laser projector; 1.0" LCD panels; Blue Laser + Phosphor Light Source; HDBaseT input; 4K Scaler; IP6X compliant sealed optical engine; Full 360° installation capability
Display Technology	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD
Price (MSRP)	$5,050 / $5,750	$9,795	$10,150 / $12,600	$18,150	$27,200	$35,550
Brightness	7,300 lumens	9,000 lumens	9,000 lumens / 10,000 lumens	13,000 lumens	17,000 lumens	20,000 lumens
Native Resolution	1080p with 4K Enhancement	WUXGA with 4K Enhancement	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)	WUXGA (1920x1200)
Max. Computer Input	4K (4096X2160)	4K (3840x2400)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)	4K (3840x2160)
Max. Video Input	1080p, 4K UHD, 4K DCI	1080p, 4K UHD, 4K DCI	1080p	1080p	1080p	1080p
Contrast Ratio	5,000,000:1	5,000,000:1	100,000:1	100,000:1	3,000,000:1	3,000,000:1
Panel Size (Diagonal)	0.64" inorganic	0.64" inorganic	0.76" inorganic	0.76" inorganic	1.0" inorganic	1.0" inorganic
Lens Type (Throw: Width)	C735P: 1.2-2.0:1 C735PS: 0.68-0.82:1	Supplied without lens	Supplied without lens	Supplied without lens	Supplied without lens	Supplied without lens
Lens Shift	C735P: Up 66%; L/R 29% C735PS: Up 50%; L/R 23%	Lens Shift: Up 50%; L/R 23%	U/D +50-10%; L/R 20%	U/D +50-10%; L/R 20%	U/D 65%; L/R 25%	U/D 65%; L/R 25%
Keystone Correction	U/D 30°; L/R 25°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°	U/D 30°; L/R 30°
Inputs	HDMI x 2; HDBaseT RJ45 x 1; USB-A x 2	HDMI x 2; DVI-D (w/ HDCP) x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;	HDMI x 2; DVI-D (w/ HDCP) x 1; Dsub15 x 1; HDBaseT RJ45 x 1; 3G-SDI BNC x 1; USB-A x 1; USB-B x 1; MiniStereo x 1;
Outputs	MiniStereo x 1; SPDIF x 1	HDMI x 1; MiniStereo x 1	HDMI x 1; Dsub15 x 1; MiniStereo x 1	HDMI x 1; Dsub15 x 1; MiniStereo x 1	HDMI x 1; MiniStereo x 1	HDMI x 1; MiniStereo x 1
Sound System	16 Watt; 1.4" Speaker x 1	-	-	-	-	-
Network Control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control	Wired LAN monitor & control
Warranty	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*	3 Years*
Light Source Life	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours	Up-to 20,000 hours
Fan Noise	As low as 29 dBa	As low as 27 dBa	As low as 27 dBa	As low as 27 dBa	As low as 40 dBa	As low as 33 dBa
Air Filter	Standard	-	-	-	-	-
Maximum Pitch	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°	Up-to 360°
Weight	17.4 lb (7.9 kg)	40.8 lb (18.5 kg)	52.9 lb (24 kg)	52.9 lb (24 kg)	63.7 lb (28.9 kg)	84.9 lb (38.5 kg)
Ceiling Mount PN	0173-4293	0173-5042	0173-5049	0173-5049	0173-5049	0173-5049

Eiki International, Inc.
22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 · Tel: 800-242-3454 · E-Mail: usa@eiki.com · Website: www.eiki.com

Prices and specifications are subject to change without notice. *Projector Warranty: 3 Years or 6,000 Hours (whichever occurs first). See warranty card for full details.