



S1002P

9,000 Lumens / 3LCD / Laser Light Engine
WUXGA with 4K Enhancement
Crestron RoomView™ & AMX Device Discovery Technology

S1002P

9,000 center lumens bright with 80% uniformity and a 5,000,000:1 contrast ratio.
WUXGA with 4K Enhancement doubles HD video resolution for sharper picture.
Compatible with inputs up-to UXGA, WUXGA and 4K.
Supports digital video input in all color standards up-to 4K (3840x2400@60Hz).
Horizontal, Vertical, Corner Keystone, & 6 point Geometric Correction.
Pincushion & Barrel and Rotation Correction. Edge Blending.
Horizontal & Vertical Manual Lens Shift. Wired network control.
Displays 4:3, 16:9 and 16:10 aspect ratios. Supports most HDTV resolutions.
Low maintenance filter-less design with sealed optical engine.
Auto input selection. Built-in Test Patterns.
Security bar. Kensington® MicroSaver® security slot. PIN lock.
3 year Projector warranty. 20,000 hour Laser Light Engine warranty.



Included Accessories:

Quick Start Guide, 5.0 ft (1.5 m) HDMI Cable, 6.0 ft (1.8 m) Detachable Power Cord, Remote Control

Optional Accessories:

Ceiling Mount, Ceiling Post and Plate

Specifications: Model S1002P

Brightness	9,000 Center Lumens	Image Signal Resizing	Smart Scaling Technology
Contrast Ratio	5,000,000:1	Image Signal Inputs	
Illumination Uniformity	80%	Digital Video (w/ HDCP)	HDMI x 2
Resolution and Aspect Ratio	WUXGA (1920x1200) with 4K Enhancement, 16:10	Digital Video (w/ HDCP)	DVI-D x 1
Color Reproduction	10-bit (16.7 million colors)	HDBaseT	RJ45 x 1
Projection Light Source	Laser (Blue) + Phosphor	3G-SDI	BNC x 1
Estimated Light Source Life	20,000 hours	USB-A - Memory Viewer	USB Type A x 1
Total Pixels	6,912,000 (1920x1200) x 3	USB-B - USB Display / Firmware	USB Type B x 1
Imaging System	0.64 in (16 mm) inorganic LCD Panels x 3	Audio Signal Inputs	
Scanning Frequency	Auto: H Sync. 15-135 KHz, V Sync. 24-88 Hz	Computer Audio	MiniStereo x 1
Pixel Clock	up-to 600 MHz	Outputs	
Lens	Optional Lenses Available - See lens chart	Digital Video	HDMI x 1
Image Diagonal	30-300" / 50-500" depending on lens	Audio Output	Variable, Stereo: MiniStereo x 1
Throw Distance	2.3-105.0 ft (0.7-32 m)	Fan Noise (Eco / Normal)	27 dB / 34 dB
Lens Shift	Manual V: +50% H: +/- 23%	Cabinet Size (HxWxD) - excluding lens	8.1 x 20.1 x 19.3 in (20.5 x 51.0 x 49.0 cm)
Projector Elevation Adjustment (legs)	Up-to 1°	Weight - without lens	40.8 lb (18.5 kg)
Maximum Pitch	Up-to 360° Installation	Packaged Cabinet Size (HxWxD)	17.3 x 29.1 x 31.5 in (44.0 x 74.0 x 80.0 cm)
Vert/Horiz. Keystone Correction	Digital: V: +/- 30° H: +/- 30°, Corner Keystone	Packaged Weight	61.7 lb (28.0 kg)
Image Orientation	Normal, Reversed, Inverted	Operating Temperature	32-122°F (0-50°C)
Local Control / Power Management	Full Function / Auto Shutdown	Electrical Safety Compliance	IEC / UL / cUL
Remote Control	Wireless / Wired x 2 (In/Out)	Electromagnetic Compatibility	FCC Class B, CE Mark
RS-232/RS-485 Control	Dsub9 x 2 (In/Out), DMX512 x 1	Power Requirements	100-240V AC, 50/60 Hz
LAN Port	RJ45 x 1	Power Consumption	0.5 W in Eco Standby mode, up-to 630 W
Computer Input in Pixels	up-to 1600x1200 (4:3), 3840x2400 (16:10)	Heat	2,150 BTU
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA	Security Facilities	Kensington® Security Slot
Digital Wide Inputs	4K, WUXGA, WSXGA+, WXGA	Limited Warranty: to the original end use customer only	
Video Formats	NTSC / PAL / SECAM	Projector	*3 years / 6,000 hours
Video Input Digital	480p, 576p, 720p, 1080i/p, 4K UHD, 4K DCI	Laser Light Engine only	*3 years / 20,000 hours use *(whichever occurs first)

EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.

Specifications subject to change without notice. © Eiki International Inc. Issued August 19, 2026
Eiki International Inc., 22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 Tel: 800-242-3454 Email: usa@eiki.com