



Projectors... and More!

LC-WB200A

3,000 ANSI lumens bright with 85% uniformity and a 2000:1 contrast ratio. Native WXGA resolution. Compatible with inputs up-to UXGA and WUXGA. Supports analog and digital video input in all color standards up-to 1080p. Convenient mid-range (1.6:1) manual zoom and focus lens. Fixed image offset. Automatic vertical digital keystone correction. Wired network monitoring and control. Digital zoom: 50% to 400%. Accepts composite, component, and S-Video in all major standards. Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions. Built-in 10 Watt sound system. Closed Caption decoding (NTSC). Variable power management option. Optional local or remote keylock. Custom warm-up screen option. Colorboard modes. Wireless remote control. Quiet operation: fan noise as low as 29 dBA. 3 year projector warranty.

LC-WB200A

3,000 ANSI Lumens / WXGA / 3LCD
"Brilliant" Series Projector

Low Power Consumption in Standby Eco
High Speed Wide Range Zoom Lens
Wired LAN Connection



Included Accessories:

Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 7.5 ft (2.3 m) Detachable Power Cord, Wireless Remote Control (with 2 AAA Batteries), Network Software on CD-ROM, Lens Cover, Filter Cover for Ceiling Mount, Soft Carry Bag.

Optional Accessories:

Replacement Lamp, Component Video Input Cable (Dsub15 to 3RCA), Ceiling Mount, Ceiling Post and Plate.

Specifications: Model LC-WB200A

Brightness	up-to 3,000 ANSI Lumens	Image Signal Inputs	
Contrast Ratio	up-to 2000:1	Computer 1 / Component (w/ optional adapter)	Dsub15 x 1
Illumination Uniformity	85%	Computer 2 (switchable Monitor out)	Dsub15 x 1
Resolution and Aspect Ratio	WXGA (1280 x 800), 16:10	Digital Video (w / HDCP)	HDMI x 1
Color Reproduction	10 bit digital / 8 bit analog	Composite Video	RCA x 1
Projection Lamp	245 Watts UHP	S-Video	S-Video x 1
Estimated Lamp Life	up-to 5,000 hours	Audio Signal Inputs	
Total Pixels	3,072,000 (1280x800) x 3	Computer Audio / Microphone Input	Stereo: MiniStereo x 2
Imaging System	0.59 in (15 mm) Inorganic LCD Panels x 3	Video Audio	RCA x 2 (L/R)
Scanning Frequency	Auto: H Sync. 15-100 kHz, V Sync. 50-100 Hz	Outputs	
Pixel Clock	up-to 140 MHz	Computer Monitor (Computer 2)	Dsub15 x 1
Lens	Attached - Manual Zoom and Focus	Audio Output	Variable, Stereo: MiniStereo x 1
Lens Specs	Speed: f: 1.6-2.33; FL: 0.609-0.965 in (15.5-24.5 mm)	Amplifier	Mono: 10 Watt
Lens Ratios	Zoom Max:Min: 1.6:1; Throw:Width 1.18-1.91:1	Speaker	1.4 in (3.7 cm) x 1 (Mono)
Image Diagonal	30-300 in (76-762 cm)	Fan Noise	as low as 29 dBA
Image Width	2.0-20 ft (0.61-6.1 m)	Cabinet Size (HxWxD) - excluding legs and lens	3.44 x 13.77 x 10.0 in (8.74 x 35 x 25.4 cm)
Throw Distance	2.3-24 ft (0.7-7.2 m)	Weight	7.5 lb (3.4 kg)
Projector Elevation Adjustment (legs)	up-to 12° Up	Packaged Cabinet Size (HxWxD)	7.7 x 17.1 x 16 in (19.8 x 43.4 x 40.6 cm)
Maximum Pitch	up-to 30° Up or Down	Packaged Weight	13.0 lb (5.9 kg)
Anti Keystone	Fixed Image Offset, Ratio (Top/Bottom) 49:1	Operating Temperature	41-95°F (5-35°C)
Vertical Keystone Correction	Digital: up-to 30° Up or Down	Electrical Safety Compliance	IEC / UL / cUL
Image Orientation	Normal, Reversed, Inverted	Electromagnetic Compatibility	FCC Class B, CE Mark
Local Control / Power Management	Full Function / Auto Shutdown	Power Requirements	100-240V AC, 50/60 Hz
Remote Control	Wireless x 1	Power Consumption	0.5 W in Eco Standby mode, up-to 322 W
RS-232 Control	Dsub9 x 1	Heat	up-to 1,179 BTU/hr
LAN Port	RJ45 x 1	Security Facilities	Kensington® Security Slot
Computer Input in Pixels	up-to 1600x1200 (4:3), 1920x1200 (16:10)	UPC	4571194675153
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	User Maintenance	Clean Filter, Replace Lamp
Analog Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	Limited Warranty: to the original end use customer only	
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	Projector	3 years
Digital Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	Lamp	6 months ownership / 500 hours use (whichever occurs first)
Video Formats	NTSC / PAL / SECAM / NTSC 4:43 / PAL-M&N		
Video Input Analog	480i/p, 575i/p		
Video Input Digital	480p, 575p, 720p, 1035i, 1080i/p		
Image Signal Resizing	Smart Scaling Technology		

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.
Eiki® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.

Specifications subject to change without notice. ©2013 Eiki International Inc. Issued May 8, 2013
Eiki International Inc., 30251 Esparanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, Email: usa@eiki.com
In Canada: 310 First St., Unit 2, P.O. Box 156, Midland ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, Email: canada@eiki.com