


## Projectors... and more!

## LC-XB250W

4,000 ANSI lumens bright with 85% uniformity and a 2000:1 contrast ratio. Native XGA resolution. Compatible with inputs up-to UXGA and WUXGA. Supports analog and digital video input in all color standards up-to 1080i. Convenient mid-range (1.6:1) manual zoom and focus lens. Fixed image offset. Automatic vertical digital keystone correction. Accepts composite, component, and S-Video in all major standards. Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions Built-in 10 Watt sound system. Closed Caption decoding (NTSC). Wired network monitoring and control. Digital zoom: 50% to 400%. Variable power management option. Optional local or remote keylock. VGA and DVI-I computer inputs, and VGA computer monitor output. Wireless remote control. Quiet operation: fan noise as low as 29 dBA. 3 year projector warranty.

## LC-XB250W

"W" for new white cabinet 4,000 ANSI Lumens / XGA / 3LCD "Brilliant" Series Projector Low Power Consumption in Standby Eco High Speed Wide Range Zoom Lens Wired LAN Connection



Included Accessories: Quick Start Guide, Owner's Manual on CD-ROM, Power Cord, VGA Computer Input Cable (Dsub15 to Dsub15), Wireless Remote Control (with 2 AAA Batteries) Network Software on CD-ROM, Soft Carry Bag, Lens Cover, Filter cover for ceiling mount.

Optional Accessories: Replacement Lamp, Component Video Input Cable (Dsub15 to 3RCA), Ceiling Mount, Ceiling Post & Plate.

## 005015104510N0 M . . . . 0 VD050NV

SPECIFICATIONS: Model LC-XB250W			
Brightness	up-to 4,000 ANSI Lumens	Image Signal Resizing	Smart Scaling Technology
Contrast Ratio	up-to 2,000:1	Image Signal Inputs	
Illumination Uniformity (corner to center) 85%		1 Computer Analog / Component (w / optional adapter) Dsub15 x 1	
Resolution and Aspect Ratio	XGA (1024x768), 4:3	2. Computer Digital & Analog	/ Digital Video w/ HDCP DVI-I x 1
Color Reproduction	8-bit (16.7 million colors)	3. Composite Video	RCA x 1
Projection Lamp	245 Watts UHP	4. S-Video	S-Video x 1
Estimated Lamp Life	up-to 5,000 Hours	Audio Signal Inputs	
Total Pixels	2,359,296 ((1024x768) x 3)	For Inputs 1 & 2 / Microphon	e Input Stereo: MiniStereo x 2
Imaging System	0.63" (16mm) inorganic LCD Panels x 3	For Inputs 3 & 4	Stereo: RCA x 2
Scanning Frequency	Auto: H: 15-100 kHz; V: 50-100 Hz	Outputs	
Pixel Clock	up-to 140 MHz	Computer Monitor	Dsub15 x 1
Lens	Attached - Manual Zoom and Focus	Audio Output	Variable, Stereo: MiniStereo x 1
	5-2.33; FL: 0.609-0.966 in (15.5-24.5 mm)	Amplifier	Mono: 10 Watt
	n Max:Min: 1.6:1; Throw:Width 1.18-1.91:1	Speaker	1.46 in (3.7 cm) x 1 (Mono)
Image Diagonal	30-300 in (76-762 cm)	Fan Noise	as low as 29 dBA
Image Width	2.0-20 ft (0.61-6.1 m)	Cabinet Size (HxWxD)	3.44 x 13.77x 10 in (8.74 x 35 x 25.4 cm)
Throw Distance	2.3-24 ft (0.7-7.2 m)		(excluding legs and lens)
Projector Elevation Adjustmen		Weight	7.5 lb (3.4 kg)
Maximum Pitch	up-to 30° Up or Down	Packaged Size (HxWxD)	7.8 x 17.1 x 16 in (19.8 x 43.4 x 40.6 cm)
	Fixed Image Offset, Ratio (Top/Bottom) 9:1	Packaged Weight	13.0 lb (5.9 kg)
Vertical Keystone Correction	Digital: up-to 30° Up or Down	Power Requirements	100-240V AC, 50/60 Hz
Image Orientation	Normal, Reversed, Inverted	Power Consumption	0.5 W in Eco Standby mode, up-to 322 W
Local Control / Power Manage		Heat	up-to 1,179 BTU/hr
RS232 Control Port	Dsub9 x 1	Power Cord	2.3 m (7.5 ft), IEC type C13, Detachable
Remote Control	Wireless (Infra Red) x 1	Electrical Safety Compliance	IEC / UL / cUL
LAN Port	RJ45 x 1	Electromagnetic Compatibility	FCC Class B, CE Mark
	up-to 1600x1200 (4:3), 1920x1200 (16:10)	Security Facilities	Kensington® Security Slot
	, SXGA+, SXGA, XGA, SVGA, VGA, MAC	Operating Temperature	41-95°F (5-35°C)
Analog Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	Air Filter	User-Clean Filter
Digital 4x3 Inputs	SXGA+, SXGA, XGA, SVGA, VGA	UPC	4571194675191
Digital Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	User Maintenance	Replace Air Filter, Change Lamp
	C / PAL / SECAM / NTSC 4.43 / PAL-M&N	Limited Warranty: to the original end-use customer only	
Video Input Analog	480i/p, 575i/p, 720p, 1035i, 1080i	Projector	3 years
Video Input Digital	480p, 575p, 720p, 1035i, 1080i	Lamp 6 months ownersh	ip / 500 hours use (whichever occurs first)